

1 LOCATION OF WATER WELL: County: <u>Sedgwick</u>		Fraction: <u>SW 1/4 NE 1/4 NE 1/4</u>	Section Number: <u>29</u>	Township Number: <u>T 27 S</u>	Range Number: <u>R 1 EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>See Below</u>					
2 WATER WELL OWNER: <u>Inttrust Bank</u>		RR#, St. Address, Box #: <u>501 Maybelle</u>			
City, State, ZIP Code: <u>Wichita, KS</u>		Board of Agriculture, Division of Water Resources Application Number: <u>80</u>			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>80</u> ft. ELEVATION: <u>6-27-96</u>			
		Depth(s) Groundwater Encountered: <u>29</u> ft. 2. <u>29</u> ft. 3. <u>29</u> ft.			
		WELL'S STATIC WATER LEVEL: <u>29</u> ft. below land surface measured on mo/day/yr <u>6-27-96</u>			
		Pump test data: Well water was <u>20</u> gpm. Well water was <u>80</u> ft. after <u>11</u> hours pumping <u>80</u> gpm.			
		Bore Hole Diameter: <u>11</u> in. to <u>80</u> ft. and <u>80</u> in. to <u>80</u> ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u>X</u>		If yes, mo/day/yr sample was submitted: <u>80</u>			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued <u>X</u> Clamped <u>X</u>			
1 Steel 3 RMP (SR)		Welded <u>X</u>			
2 PVC 4 ABS		Threaded <u>X</u>			
Blank casing diameter: <u>5</u> in. to <u>70</u> ft. Dia. <u>2.60</u> in. to <u>100</u> ft. Dia. <u>100</u> PSI					
Casing height above land surface: <u>12</u> in. weight <u>2.60</u> lbs./ft. Wall thickness or gauge No. <u>100</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify) <u>100</u>			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) <u>80</u>					
SCREEN-PERFORATED INTERVALS: From <u>70</u> ft. to <u>80</u> ft. From <u>80</u> ft. to <u>80</u> ft.					
GRAVEL PACK INTERVALS: From <u>28</u> ft. to <u>80</u> ft. From <u>80</u> ft. to <u>80</u> ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other <u>80</u>					
Grout Intervals: From <u>3</u> ft. to <u>28</u> ft. From <u>28</u> ft. to <u>80</u> ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage <u>80</u>					
Direction from well? <u>Nest</u>		How many feet? <u>80</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	22	clay			
22	40	fine sand			
40	41	clay			
41	80	fine to medium sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>6-27-96</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>318</u> This Water Well Record was completed on (mo/day/yr) <u>7-10-96</u> under the business name of <u>Weninger Drilling, Inc</u> by (signature) <u>Kenneth P. Brenner</u>					