


1 LOCATION OF WATER WELL: County: Sedgwick	Fraction SW 1/4 NE 1/4 SE 1/4	Section Number 26	Township Number T 27 S	Range Number R 1 E
--	---	-----------------------------	----------------------------------	------------------------------

Distance and direction from nearest town or city street address of well if located within city?

1029 South West Street, Wichita, Kansas

2 WATER WELL OWNER: Batson Properties	Paragon NDT & Finishes Inc.	01968021	MW-4S
RR#, St. Address, Box # : 1029 S. West Street	1015 S. West Street	Board of Agriculture, Division of Water Resources	
City, State, ZIP Code : Wichita, KS 67213	Wichita, KS 67213	Application Number:	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 20 ft. ELEVATION: Approx. 1299 Depth(s) Groundwater Encountered 1. 14 ft. 2. 14 ft. 3. 14 ft. WELL'S STATIC WATER LEVEL 13.3 ft. below land surface measured on mo/day/yr 11/11/96 Pump test data: Well water was N/A ft. after N/A hours pumping N/A gpm Est. Yield N/A gpm: Well water was N/A ft. after N/A hours pumping N/A gpm Bore Hole Diameter 8.25 in. to 20 ft. and 20 in. to 20 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted No Water Well Disinfected? Yes No X
--	---

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS Blank casing diameter 2 in. to 10 ft. Dia 2 in. to 10 ft. Dia 2 in. to 10 ft. Dia 2 in. to 10 ft. Dia Casing height above land surface -2 in. weight -2 lbs./ft. Wall thickness or gauge No. Sch 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole) SCREEN-PERFORATED INTERVALS: From 10 ft. to 20 ft. From 10 ft. to 20 ft. From 10 ft. to 20 ft. From 10 ft. to 20 ft. GRAVEL PACK INTERVALS: From 7 ft. to 20 ft. From 7 ft. to 20 ft. From 7 ft. to 20 ft. From 7 ft. to 20 ft.
--

6 GROUT MATERIAL: 1 Neat cement Grout Intervals: From 0 ft. to 5 ft. From 5 ft. to 7 ft. From 7 ft. to 7 ft. From 7 ft. to 7 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage

Direction from well?		How many feet?	
FROM	TO	LITHOLOGIC LOG	PLUGGING INTERVALS
0	0.5	Concrete Pavement & Crushed Limestone Subgrade	
0.5	6	Silty Lean Clay	
6	9	Clayey Fine Sand	
9	14	Fine Sand With Clay	
14	20	Medium Sand	

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/17/96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 11-18-96 under the business name of Terracon Consultants, Inc. by (signature) <i>Steve Freese</i>
