

1 LOCATION OF WATER WELL: County: <u>Sedgwick</u>		Fraction <u>NW ¼ SW ¼ NW ¼</u>	Section Number <u>35</u>	Township Number T <u>27</u> S	Range Number R <u>1</u> E <u>(2)</u>
Distance and direction from nearest town or city street address of well if located within city? <u>1850 S. Hoover, Wichita KS</u>					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code : <u>Utility Contractors</u> <u>PO BOX 2079</u> <u>Wichita KS 67201</u>					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>13</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. .ft. 2. .ft. 3. .ft.			
		WELL'S STATIC WATER LEVEL <u>10.06</u> ft. below land surface measured on mo/day/yr <u>11-7-96</u>			
		Pump test data: Well water was .ft. after . hours pumping gpm			
		Est. Yield gpm Well water was .ft. after . hours pumping gpm			
		Bore Hole Diameter <u>8</u> in. to .ft., and .in. to .ft.			
		WELL WATER TO BE USED AS: 1 Domestic <u>was</u> 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <u>10 Monitoring well</u>			
		Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> . If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No <u>X</u>			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
<u>2 PVC</u>		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded <u>Flush</u>
			7 Fiberglass		<u>Threaded</u>
Blank casing diameter <u>2</u> in. to .ft., Dia .in. to .ft., Dia .in. to .ft.					
Casing height above land surface <u>Flush</u> in., weight <u>70.3</u> lbs./ft. Wall thickness or gauge No. <u>15.4</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		<u>3 Mill slot</u>	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From <u>3</u> ft. to <u>13</u> ft., From .ft. to .ft.					
GRAVEL PACK INTERVALS: From <u>2</u> ft. to <u>13</u> ft., From .ft. to .ft.					
FROM .ft. TO .ft. FROM .ft. TO .ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout <u>3 Bentonite</u> 4 Other					
Grout Intervals: From <u>2</u> ft. to <u>1</u> ft., From .ft. to .ft., From .ft. to .ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	<u>11 Fuel storage</u>	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	13 Insecticide storage	16 Other (specify below)
Direction from well? <u>SW</u> How many feet? <u>75</u>					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
			<u>3</u>	<u>13</u>	<u>Bentonite</u>
			<u>0</u>	<u>3</u>	<u>Concrete</u>
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or <u>(3) plugged</u> under my jurisdiction and was completed on (mo/day/year) <u>11-7-96</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>531</u> This Water Well Record was completed on (mo/day/yr) <u>11-11-96</u> under the business name of <u>GSI</u> by (signature) <u>[Signature]</u>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					