

1 LOCATION OF WATER WELL: County: Sedgewick NW 1/4 NE 1/4 NNW 1/4 Section Number 30 Township Number T 27 S Range Number R 1 E/W

Distance and direction from nearest town or city street address of well if located within city? 11615 Kent

2 WATER WELL OWNER: Chuck Chestnut RR#, St. Address, Box #: 520 S. Holland Suite #105 City, State, ZIP Code: Wichita, KS 67209 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the NW section]

4 DEPTH OF COMPLETED WELL: 65 ft. ELEVATION: 29 ft. below land surface measured on mo/day/yr 2-3-97

WELL'S STATIC WATER LEVEL: 29 ft. below land surface measured on mo/day/yr 2-3-97

Pump test data: Well water was 11 in. to 65 ft. and 65 ft. Dia. 2.40 in. weight 160RST

Est. Yield 20 gpm: Well water was 11 in. to 65 ft. and 65 ft. Dia. 2.40 in. weight 160RST

Bore Hole Diameter: 11 in. to 65 ft. and 65 ft. Dia. 2.40 in. weight 160RST

WELL WATER TO BE USED AS: 1 Domestic, 2 Irrigation, 3 Feedlot, 4 Industrial, 5 Public water supply, 6 Oil field water supply, 7 Lawn and garden only, 8 Air conditioning, 9 Dewatering, 10 Monitoring well, 11 Injection well, 12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel, 2 PVC, 3 RMP (SR), 4 ABS, 5 Wrought iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below), 10 Asbestos-cement, 11 Other (specify), 12 None used (open hole)

Blank casing diameter: 5 in. to 56 ft. Dia. 2.40 in. weight 160RST

Casing height above land surface: 2 in. weight 160RST

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Stainless steel, 4 Galvanized steel, 5 Fiberglass, 6 Concrete tile, 7 PVC, 8 RMP (SR), 9 ABS, 10 Asbestos-cement, 11 Other (specify), 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 2 Louvered shutter, 3 Mill slot, 4 Key punched, 5 Gauzed wrapped, 6 Wire wrapped, 7 Torch cut, 8 Saw cut, 9 Drilled holes, 10 Other (specify), 11 None (open hole)

SCREEN-PERFORATED INTERVALS: From 56 ft. to 65 ft. From 29 ft. to 65 ft. From 29 ft. to 65 ft. From 29 ft. to 65 ft.

GRAVEL PACK INTERVALS: From 29 ft. to 65 ft. From 29 ft. to 65 ft. From 29 ft. to 65 ft. From 29 ft. to 65 ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other

Grout Intervals: From 3 ft. to 29 ft. From 29 ft. to 65 ft. From 29 ft. to 65 ft. From 29 ft. to 65 ft.

What is the nearest source of possible contamination: 1 Septic tank, 2 Sewer lines, 3 Watertight sewer lines, 4 Lateral lines, 5 Cess pool, 6 Seepage pit, 7 Pit privy, 8 Sewage lagoon, 9 Feedyard, 10 Livestock pens, 11 Fuel storage, 12 Fertilizer storage, 13 Insecticide storage, 14 Abandoned water well, 15 Oil well/Gas well, 16 Other (specify below)

Direction from well? Northeast

How many feet? 14

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-3-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 2-4-97 under the business name of Weninger Drilling Inc. by (signature) Michele

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.