

1 LOCATION OF WATER WELL:		FRACTION		Water Well Record Form WWC-5	KSA 87a-1212	Section Number	Township Number	Range Number
Sedgwick		SE 1/4 SE 1/4 NE 1/4				29	T 27 S	R 1W E/W
Distance and direction from nearest town or city street address of well if located within city?								
571 S. Tyler Wichita, Kansas								
WATER WELL OWNER: TYLER ROAD BAPTIST CHURCH								
RR#, ST. ADDRESS, BOX #: 571 S. Tyler								
CITY, STATE, ZIP CODE: Wichita, Kansas								
Board of Agriculture, Division of Water Resource Application Number:								
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 105 ft. ELEVATION:						
		Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.						
		WELL'S STATIC WATER LEVEL 35 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 04/02/1997						
		Pump test data: Well water was ft. after hours pumping gpm						
		Est. Yield gpm: Well water was ft. after hours pumping gpm						
		Bore Hole Diameter 12 in. to 105 ft. and in. to ft.						
WELL WATER TO BE USED AS:								
1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well								
2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)								
7 Lawn and garden only 10 Monitoring well								
Was a chemical/bacteriological sample submitted to Department? Yes No ☒ ; If yes, mo/day/yr sample was submitted								
Water Well Disinfected? Yes ☒ No								
5 TYPE OF CASING USED:								
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ☒ Clamped								
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (Specify below) Welded								
7 Fiberglass SDR-26 Threaded								
Blank casing Diameter 5 in. to 85 ft., Dia in. to ft., Dia in. to ft.								
Casing height above land surface 12 in., weight 2.35 lbs. / ft. Wall thickness or gauge No. .214								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)								
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)								
SCREEN OR PERFORATION OPENING ARE:								
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)								
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes								
7 Torch cut 10 Other (specify)								
SCREEN-PERFORATION INTERVALS: from 85 ft. to 105 ft., From ft. to ft.								
GRAVEL PACK INTERVALS: from 24 ft. to 105 ft., From ft. to ft.								
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other								
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft.								
What is the nearest source of possible contamination:								
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandon water well								
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well								
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)								
13 Insecticide storage None Apparent								
Direction from well? How many feet?								
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS			
0	2	topsoil						
2	15	clay						
15	80	medium to coarse sand and gravel						
80	84	clay						
84	105	medium to coarse sand, white in color						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 04/02/1997 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 04/04/97 Under the business name of Harp Well & Pump Service, Inc. by (signature) Todd S. Harp								