

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Sedgwick		SE 1/4 NW 1/4 NW 1/4		03		T 27 S		R 1 EW	
Distance and direction from nearest town or city street address of well if located within city? 2806 N. Ridge Road Wichita, KS									
2 WATER WELL OWNER: Rich-Mix Products Inc.--Kansas Division									
RR#, St. Address, Box # : 2806 N. Ridge Road									
City, State, ZIP Code : Wichita, KS 67205									
Board of Agriculture, Division of Water Resources									
Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:									
4 DEPTH OF COMPLETED WELL: 18 ft. ELEVATION: Approx. 1307 MSL									
Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.									
WELL'S STATIC WATER LEVEL 10 ft. below land surface measured on mo/day/yr 1980									
Pump test data: Well water was ft. after hours pumping gpm									
Est. Yield gpm: Well water was ft. after hours pumping gpm									
Bore Hole Diameter 1.25 in. to 20 ft. and in. to ft.									
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well									
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)									
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well									
Was a chemical/bacteriological sample submitted to Department? Yes No XX If yes, mo/day/yr sample was sub-									
mitted									
Water Well Disinfected? Yes No									
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped									
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded XX									
7 Fiberglass Threaded									
Blank casing diameter 1.25 in. to 16 ft. Dia in. to ft. Dia in. to ft.									
Casing height above land surface in. weight lbs./ft. Wall thickness or gauge No.									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement									
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)									
9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes									
7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 16 ft. to 18 ft. From ft. to ft.									
From ft. to ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From ft. to ft. From ft. to ft.									
From ft. to ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout intervals: From 0 ft. to 0.5 ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
13 Insecticide storage									
Direction from well? North Northwest How many feet? +80 feet									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
RECEIVED									
BUREAU OF WATER									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1980 and this record is true to the best of my knowledge and belief. Kansas									
Water Well Contractor's License No. This Water Well Record was completed on (mo/day/yr) March 1997									
under the business name of Rich-Mix Products, Inc. by (signature) Steve Street									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									