


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK		SE 1/4 NW 1/4 NW 1/4	03	T 27 S	R 1 E/W
Distance and direction from nearest town or city street address of well if located within city? 2806 N. RIDGE ROAD					
2 WATER WELL OWNER: Rich-Mix Products Inc.--Kansas Division					
RR#, St. Address, Box # :			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code :			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 20 ft. ELEVATION: Approx. 1305 MSL			
N 1 Mile W E S 		Depth(s) Groundwater Encountered 1. .ft. 2. .ft. 3. .ft.			
		WELL'S STATIC WATER LEVEL 10 ft. below land surface measured on mo/day/yr 1981			
		Pump test data: Well water was .ft. after . hours pumping . gpm			
		Est. Yield . gpm: Well water was .ft. after . hours pumping . gpm			
		Bore Hole Diameter . 1.25 in. to 20 .ft., and . in. to .ft.			
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well					
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes. No. XX; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped					
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded					
Blank casing diameter 1.25 in. to 18 .ft., Dia . in. to .ft., Dia . in. to .ft.					
Casing height above land surface . in., weight . lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)					
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 18 ft. to 20 ft., From .ft. to .ft.					
GRAVEL PACK INTERVALS: From .ft. to .ft., From .ft. to .ft.					
From .ft. to .ft., From .ft. to .ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 0.5 ft., From .ft. to .ft., From .ft. to .ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? North Northeast How many feet? +80 feet					
FROM	TO	LITHOLOGIC LOG		FROM	TO
PLUGGING INTERVALS					
RECEIVED BUREAU OF WATER					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1981 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. This Water Well Record was completed on (mo/day/yr) March 1997 under the business name of Rich-Mix Products, Inc. by (signature) Steve Stuart					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4