

1 LOCATION OF WATER WELL:		FRACTION		Section Number		Township Number		Range Number	
Sedgwick		SW 1/4 SW 1/4 NW 1/4		4		T 27 S		R 1W E/W	
Distance and direction from nearest town or city street address of well if located within city?									
8613 Meadow Pass Ct. Wichita, Kansas									
WATER WELL OWNER:		GOENTZEL HOMES							
RR#, ST. ADDRESS, BOX #:		8613 Meadow Pass Ct.							
CITY, STATE, ZIP CODE:		Wichita, Kansas							
		Board of Agriculture, Division of Water Resource							
		Application Number:							
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL		80 ft.		ELEVATION:			
		Depth(s) groundwater Encountered		1 ft.		2 ft.		3 ft.	
		WELL'S STATIC WATER LEVEL		30		FT. BELOW LAND SURFACE MEASURED ON		mo/day/yr	
		Pump test data:		Well water was		ft. after		hours pumping	
		Est. Yield		gpm:		Well water was		ft. after	
Bore Hole Diameter		12 in.		to 80		ft. and		in. to	
WELL WATER TO BE USED AS:		5 Public water supply		8 Air conditioning		11 Injection well			
1 Domestic		3 Feedlot		6 Oil field water supply		9 Dewatering		12 Other (Specify below)	
2 Irrigation		4 Industrial		7 Lawn and garden only		10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes		No		X		If yes, mo/day/yr sample was			
submitted		Water Well Disinfected?		Yes		X		No	
5 TYPE OF CASING USED:		5 Wrought iron		8 Concrete tile		CASING JOINTS:		Glued X Clamped	
1 Steel		3 RMP (SR)		6 Asbestos-Cement		9 Other (Specify below)		Welded	
2 PVC		4 ABS		7 Fiberglass		SDR-26		Threaded	
Blank casing Diameter		5 in.		to 60		ft., Dia		in. to	
Casing height above land surface		12 in.		weight		2.35		lbs. / ft.	
TYPE OF SCREEN OR PERFORATION MATERIAL:		5 Fiberglass		8 RMP (SR)		11 other (specify)			
1 Steel		3 Stainless Steel		6 Concrete tile		9 ABS		12 None used (open hole)	
2 Brass		4 Galvanized steel		5 Gauzed wrapped		8 Saw cut		11 None (open hole)	
SCREEN OR PERFORATION OPENING ARE:		6 Wire wrapped		9 Drilled holes		10 Other (specify)			
1 Continuous slot		3 Mill slot		7 Torch cut					
2 Louvered shutter		4 Key punched							
SCREEN-PERFORATION INTERVALS:		from 60		ft. to 80		ft., From		ft. to	
		from		ft. to		ft., From		ft. to	
GRAVEL PACK INTERVALS:		from 24		ft. to 80		ft., From		ft. to	
		from		ft. to		ft., From		ft. to	
6 GROUT MATERIAL:		1 Neat cement		2 Cement grout		3 Bentonite		4 Other bentonite hole plug	
Grout Intervals: From		4		ft. to 24		ft. From		ft. to	
What is the nearest source of possible contamination:		10 Livestock pens		14 Abandon water well					
1 Septic tank		4 Lateral lines		7 Pit privy		11 Fuel storage		15 Oil well/Gas well	
2 Sewer lines		5 Cess pool		8 Sewage lagoon		12 Fertilizer storage		16 Other (specify below)	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		13 Insecticide storage			
Direction from well?		North		How many feet?		15			
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS			
0	20	fine sand							
20	24	clay							
24	40	fine sand							
40	50	coarse sand							
50	55	clay							
55	80	medium sand							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 09/13/1997 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 09/15/97 Under the business name of Harp Well & Pump Service, Inc. by (signature) Todd S. Harp									