

SE NW SW SW

WATER WELL RECORD

Form WWC-5

KSA 82a-1212

T. 27 S.

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u>		<u>8/16</u> 1/4 <u>8/16</u> 1/4 <u>8/16</u> 1/4	<u>31</u>	T <u>27</u> S	R <u>1</u> E <u>W</u>
Distance and direction from nearest town or city street address of well if located within city? <u>10215 Haskell Wichita KS.</u>					
2 WATER WELL OWNER: <u>Tony Hoang</u> RR#, St. Address, Box # : <u>10215 Haskell</u> City, State, ZIP Code : <u>Wichita KS.</u> Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>110</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>82</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>44</u> ft. below land surface measured on mo/day/yr <u>11-19-97</u>			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>10</u> in. to <u>118</u> ft. and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial <u>7 Lawn and garden only</u> 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		Water Well Disinfected? Yes No			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ☒ Clamped			
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below) Welded			
Blank casing diameter <u>5</u> in. to <u>110</u> ft. Dia		7 Fiberglass Threaded			
Casing height above land surface <u>14</u> in. weight <u>100</u> lbs./ft. Wall thickness or gauge No. <u>26</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From <u>80</u> ft. to <u>100</u> ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>25</u> ft. to <u>110</u> ft. From ft. to ft.					
6 GROUT MATERIAL: <u>Neat cement</u> 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From <u>3</u> ft. to <u>25</u> ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? <u>West</u>		How many feet? <u>40</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	TOPSOIL			
2	17	CLAY			
17	34	FINE SAND			
34	82	CLAY			
82	97	MED-FINE SAND			
97	110	FINE SAND			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>11-19-97</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>611</u> This Water Well Record was completed on (mo/day/yr) <u>11-21-97</u> under the business name of <u>Close Drilling</u> by (signature) <u>Paul Chee</u>					

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4