

1 LOCATION OF WATER WELL: Sedgwick	FRACTION NE ^{SE} 1/4 SW 1/4 NE 1/4	Section Number 8	Township Number T 27 S	Range Number R 1W E/W
--	---	----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

1902 N. Westfield Wichita, Kansas

WATER WELL OWNER: MILANOVICH, Mary Ann	Board of Agriculture, Division of Water Resource
RR#, ST. ADDRESS, BOX #: 1902 N. Westfield	Application Number:
CITY, STATE, ZIP CODE: Wichita, Kansas	

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL 80 ft. ELEVATION:
	Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.
	WELL'S STATIC WATER LEVEL 28 FT. BELOW LAND SURFACE MEASURED ON 05/18/1999
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter 12 in. to 80 ft. and in. to ft.	
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes	No X ; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No	

5 TYPE OF CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel 3 RMP (SR)	6 Asbestos-Cement	9 Other (Specify below)	Welded
2 PVC 4 ABS	7 Fiberglass	SDR-26	Threaded
Blank casing Diameter 5 in. to 65 ft., Dia	in. to ft., Dia	in. to ft.	
Casing height above land surface 12 in., weight 2.35 lbs./ft.	Wall thickness or gauge No. .214		
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)	2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)		
SCREEN OR PERFORATION OPENING ARE:	5 Gauzed wrapped 8 Saw cut 11 None (open hole)		
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes	2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)		
SCREEN-PERFORATION INTERVALS: from 65 ft. to 80 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: from 24 ft. to 80 ft., From ft. to ft.			

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From 24 ft. to 28 ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandon water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage

Direction from well? East	How many feet? 13
FROM TO LITHOLOGIC LOG	FROM TO PLUGGING INTERVALS
0 3 topsoil	
3 17 clay	
17 21 finesand	
21 32 clay	
32 38 silty fine sand	
38 46 fine to medium sand	
46 53 clay	
53 62 fine sand with clay	
62 66 fine sand	
66 80 fine to medium sand	

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 05/18/1999 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 05/19/99
Under the business name of Harp Well & Pump Service, Inc. by (signature) Todd S. Harp