

1	LOCATION OF WATER WELL:	FRACTION	Section Number	Township Number	Range Number
	Sedgwick SE	SE 1/4 NE 1/4 SW 1/4	3	T 27 S	R 1W E/W

Distance and direction from nearest town or city street address of well if located within city?

6410 Clear Meadow Wichita, Kansas

WATER WELL OWNER: GREEN, Michelle

RR#, ST. ADRESS, BOX # : 6410 Clear Meadow


CITY, STATE, ZIP CODE : Wichita, Kansas

Board of Agriculture, Division of Water Resource

Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4	DEPTH OF COMPLETED WELL	40	ft.	ELEVATION:	
	Depth(s) groundwater Encountered	1	ft.	2	ft.
	WELL'S STATIC WATER LEVEL	10	FT. BELOW LAND SURFACE MEASURED ON	mo/day/yr	07/13/1999



Pump test data:		Well water was		ft.	after	hours	pumping	gpm
Est. Yield	gpm:	Well water was		ft.	after	hours	pumping	gpm
Bore Hole Diameter	12	in.	to	40	ft.	and	in.	to
WELL WATER TO BE USED AS:		5 Public water supply		8 Air conditioning		11 Injection well		
1 Domestic	3 Feedlot	6 Oil field water supply		9 Dewatering		12 Other (Specify below)		
2 Irrigation	4 Industrial	7 Lawn and garden only		10 Monitoring well				

Was a chemical/bacteriological sample submitted to Department? Yes ☐ No ☒ ; If yes, mo/day/yr sample was submitted _____

Water Well Disinfected? Yes ☒ No ☐

5	TYPE OF CASING USED:
---	----------------------

1 Steel	3 RMP (SR)
2 PVC	4 ABS

5 Wrought iron
6 Asbestos-Cement
7 Fiberglass
8 Concrete tile
9 Other (Specify below)
SDR - 26

CASING JOINTS: Glued ☒ Clamped
 Welded
 Threaded

Blank casing Diameter 5 in. to 40 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 12 in., weight 2.35 lbs. / ft. Wall thickness or gauge No. .214

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel
2 Brass
3 Stainless Steel
4 Galvanized steel

5 Fiberglass	8 $\overline{\text{RMP}}$ (SR)
6 Concrete tile	9 ABS

10 Asbestos-cement
11 other (specify)
12 None used (open hole)

SCREEN OR PERFORATION OPENING ARE:

1 Continous slot	3 Mill slot
2 Louvered shutter	4 Key punched

5 Gauzed wrapped
6 Wire wrapped
7 Torch cut

8 Saw cut
9 Drilled holes
10 Other (specify)
11 None (open hole)

SCREEN-PERFORATION INTERVALS:	from 30	ft. to 40	ft., From	ft. to	ft.
	from	ft. to	ft., From	ft. to	ft.
GRAVEL PACK INTERVALS:	from 24	ft. to 40	ft., From	ft. to	ft.
	from	ft. to	ft., From	ft. to	ft.

6	GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other	bentonite hole plug
---	-----------------	---------------	----------------	-------------	---------	---------------------

Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	None Apparent

Direction from well?

How many feet?

[illegible]

7. **CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:** This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 07/13/1999 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 07/15/99 Under the business name of Harp Well & Pump Service, Inc. by (signature) _____

Todd S. Harp