

1 LOCATION OF WATER WELL: Sedgwick	FRACTION NW 1/4 NW 1/4 NE 1/4	Section Number 29	Township Number T 27 S	Range Number R 1W E/W
--	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

310 Mamie Wichita, Kansas

WATER WELL OWNER: BROWN, Rick	Board of Agriculture, Division of Water Resource
RR#, ST. ADDRESS, BOX #: 310 Mamie	Application Number:
CITY, STATE, ZIP CODE: Wichita, Kansas	

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL 129 ft. ELEVATION:
	Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.
	WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 07/14/1999
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter 12 in. to 129 ft. and in. to ft.	
WELL WATER TO BE USED AS:	5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes submitted	No X ; If yes, mo/day/yr sample was Water Well Disinfected? Yes X No

5 TYPE OF CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS:
1 Steel 3 RMP (SR)	6 Asbestos-Cement	9 Other (Specify below)	Glued X Clamped
2 PVC 4 ABS	7 Fiberglass	SDR-26	Welded
Blank casing Diameter 5 in. to 119 ft., Dia in. to ft., Dia in. to ft.			Threaded
Casing height above land surface 12 in., weight 2.35 lbs. / ft.			Wall thickness or gauge No. .214
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
1 Steel 3 Stainless Steel	6 Concrete tile	9 ABS	11 other (specify)
2 Brass 4 Galvanized steel			12 None used (open hole)
SCREEN OR PERFORATION OPENING ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot 3 Mill slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter 4 Key punched	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATION INTERVALS:	from 119 ft. to 129 ft., From ft. to ft.		
GRAVEL PACK INTERVALS:	from 26 ft. to 129 ft., From ft. to ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other bentonite hole plug
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandon water well		
1 Septic tank 4 Lateral lines	11 Fuel storage	15 Oil well/Gas well		
2 Sewer lines 5 Cess pool	12 Fertilizer storage	16 Other (specify below)		
3 Watertight sewer lines 6 Seepage pit	13 Insecticide storage			
9 Feedyard				
Direction from well? East	How many feet? 75			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	topsoil			
3	21	clay			
21	39	fine sand			
39	45	fine sand			
45	52	medium sand			
52	55	clay			
55	61	fine sand			
61	64	clay			
64	117	fine sand			
117	129	medium sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 07/14/1999 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 07/16/99
Under the business name of Harp Well & Pump Service, Inc. by (signature)

Todd S. Harp