1.00.			-	FRACTION	Water V	ell Record	Form WWC-5				
Ŀ	TION OF WA		/-			_		Section Number	Township Number	Range Number	
	Sedgw		SE	SW 1/4			E 1/4	3	T 27 s	R 1W E/W	
Distance and direction frem nearest town or city street address of well if located within city?											
6200 W. 21st N. Wichita, Kansas											
WAT	TER WELL O	WNER: PLA	YER	S SPORTS	BAR						
RR#, 5	ST. ADRESS,	020	0 W						Board of Agricultus	re, Divivsion of Water Resource	
CITY,	CITY, STATE, ZIP CODE: Wichita, Kansas									Application Number:	
		OCATION WITH	<u> </u>	DEPTH OF COM	IPLETED V	VELL	70	ft. El	LEVATION:		
AN "X"	IN SECTION	N BOX:		epth(s) groundwa	ter Encoun	tered	1	ft.	2 ft.	3 ft.	
Ιİ			WE	LL'S STATIC W	ATER LEV	EL 10) FT	BELOW LAND	SURFACE MEASURED ON mo/day/y	10/20/1999	
	NW	NE	1	Pump test	data:	Well w	rater was	ft.	after hours p	oumping gpm	
	!		Est.	Yield	gpm:	Well v	vater was	ft.	after hours p	oumping gpm	
M M			Bore	Hole Diameter	12	in.	to 70	ft.	and i	in. to ft.	
= "			WEL	L WATER TO E	E USED AS	S: 5	5 Public wate	r supply	8 Air conditioning	1 Injection well	
١,] :	Domestic	3 Feedlot	(6 Oil field wa	ter supply	9 Dewatering	12 Other (Specify below)	
1 1			1 2	2 Irrigation	4 Industri	ial ?	7 Lawn and g	garden only	10 Monitoring well		
		X	Was	a chemical/bacte	riological sa	ımple sul	bmitted to D	epartment? Yes	No X ; If yes	s, mo/day/yr sample was	
S submitted Water Well Disinfected? Yes X No											
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped											
1 Stee	l	3 RMP (SR)			6 Asbesto	s-Cemer	ıt 9	Other (Specify	below)	Welded	
2 PVC	2	4 ABS			7 Fibergh	255	s	DR-26		Threaded	
Blank ca	 sing Diam	eter 5	in.	to 50	ft.,	Dia	in.	to	ft., Dia in	ı. to ft.	
Casing h	eight abov	e land surface	12	in.,	W	eight 2	.35	lbs. / ft.	Wall thickness or gauge No.	.214	
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement											
1 Stee	al	3 Stainless Stee	l		5 Fibergla	5 8	8	RMP (SR)	11 other (spe	cify)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)										(open hole)	
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open he										11 None (open hole)	
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes											
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)											
SCREEN-PERFORATION INTERVALS: from 50 ft. to 70 ft., From ft. to ft.											
from ft. to ft., From ft. to ft.											
GRAVEL PACK INTERVALS: from 24						ft. to 70		ft., Fr			
				from		ft.	to	ft., Fr		144	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug											
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From 24 ft. to 26 ft.											
What is the nearest source of possible contamination:									10 Livestock pens 14 Abandon water weli		
1 Septic tank 4 Lateral lines						privy		11 Fuel	storage	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool					8 Sewage lagoon					16 Other (specify below)	
3 Watertight sewer lines 6 Seepage plt 9 Feedyard 13 Insecticide storage											
Directio	n from wel	? South							How many feet? 60		
FROM	TO		LITH	OLOGIC LOG			FROM	TO	PLUGGING IN	TERVALS	
0	4	topsoil									
4	10	trash									
10	20	medium									
20	50			rse sand							
50	68	medium	san	<u> </u>							
68	70	shale									
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and											
was c	ompleted	on (mo/day/yea	ar)	10/20/	<u> 1999</u>		and this re	cord is true to	the best of my knowledge	and belief. Kansas Water	
Well C	ontracto	's License No.	23	16	This Wate	r Well R	ecord was	completed on	(mo/day/yr)1.0./	/22/99	
Under the business name of HarpWell&PumpServiceInc by (signature)											
									Jodd.	S. Haro	