

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK		SE 1/4 SE 1/4 SW 1/4	16	T 27 S	R 1 E
Distance and direction from nearest town or city street address of well if located within city? 8000 WEST CENTRAL WICHITA, KS					
2 WATER WELL OWNER: FINA OIL & CHEMICAL, CO. RR#, St. Address, Box #: P.O. BOX 2126 DALLAS TX 75211 City, State, ZIP Code: Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 34 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 0 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter XX 8 1/4 in. to 34 ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering X 12 Other (Specify below) 7 Lawn and garden only 10 Monitoring well vapor extraction Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No			
		5 TYPE OF BLANK CASING USED:			
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped X 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass X Threaded Blank casing diameter 4 in. to 14 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 0 in. weight sched 40 lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass X 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot X 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)			
		SCREEN-PERFORATED INTERVALS: From 34 ft. to 14 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 34 ft. to 12 ft. From ft. to ft. From ft. to ft. From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement X 2 Cement grout X 3 Bentonite 4 Other					
Grout Intervals: From 9 ft. to 0.05 ft. From 12 ft. to 9 ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage X 6 Other (specify below) 13 Insecticide storage abandon ust					
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	8"	CONCRETE			
8"	4	FILL W/BRN SILTY CLAY			
4	20	BRN SILTY CLAY W/IRON & BLK MOTTELING			
20	30	BRN SILTY SLIGHTLY SANDY CLAY			
30	34	AS ABOVE 20% FINE G.SAND			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (X) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-17-98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 575 This Water Well Record was completed on (mo/day/yr) 1-2-99 99 under the business name of KURTZ ENVIRONMENTAL SERVICE by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4