

1 LOCATION OF WATER WELL: Sedgwick		FRACTION NE 1/4 NW 1/4 SE 1/4		Section Number 6	Township Number T 27 S	Range Number R 1W E/W
Distance and direction from nearest town or city street address of well if located within city? 1/2 m. N. of 21st N. & 1/4 W. of Maize Rd. Wichita, KS.						
WATER WELL OWNER: WICHITA, CITY OF		Board of Agriculture, Division of Water Resource				
RR#, ST. ADDRESS, BOX #: 455 N. Main		CITY, STATE, ZIP CODE: Wichita, Kansas		67202	Application Number: 20000235	
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF PLUGGED WELL 55 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 20 FT. BELOW LAND SURFACE MEASURED ON 6-18-2001 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm : Well water was ft. after hours pumping gpm Bore Hole Diameter was in. to ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No ☒ ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes ☒ No				
5 TYPE OF CASING USED:		CASING JOINTS:				
1 Steel 3 RMP (SR)		Glued Clamped				
2 PVC 4 ABS		Welded				
Blank casing Diameter 8 in. to ft. , Dia in. to ft. , Dia in. to 36 ft.		Threaded				
Casing height above land surface below in., weight lbs. / ft.		Wall thickness or gauge No.				
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement				
1 Steel 3 Stainless Steel		7 PVC 8 RMP (SR)				
2 Brass 4 Galvanized steel		11 other (specify) N/A				
5 Fiberglass		12 None used (open hole)				
6 Concrete tile		9 ABS				
SCREEN OR PERFORATION OPENING ARE:		8 Saw cut 11 None (open hole)				
1 Continuous slot 3 Mill slot		9 Drilled holes				
2 Louvered shutter 4 Key punched		10 Other (specify) N/A				
SCREEN-PERFORATION INTERVALS:		7 Torch cut				
from ft. to ft. , From ft. to ft.		from ft. to ft. , From ft. to ft.				
GRAVEL PACK INTERVALS:		from ft. to ft. , From ft. to ft.				
6 GROUT MATERIAL:		4 Other bentonite hole plug				
1 Neat cement 2 Cement grout 3 Bentonite		ft. From 9 ft. to 20 ft.				
Grout Intervals: From 3 ft. to 9 ft. From ft. to ft.		10 Livestock pens 14 Abandon water well				
What is the nearest source of possible contamination:		11 Fuel storage 15 Oil well/Gas well				
1 Septic tank 4 Lateral lines 7 Pit privy		12 Fertilizer storage 16 Other (specify below)				
2 Sewer lines 5 Cess pool 8 Sewage lagoon		13 Insecticide storage None Apparent				
3 Watertight sewer lines 6 Seepage pit 9 Feedyard						
Direction from well?		How many feet?				
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS
				0	3	surface clay and silt
				3	9	cement grout
				9	20	bentonite hole plug
				20	55	chlorinated sand & gravel
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-18-2001 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 6-21-2001						
Under the business name of Harp Well & Pump Service, Inc. by (signature) Todd S. Harp						