

CORRECTION TO WATER WELL RECORD (WWC-5)

The following correction(s) was made to the attached WWC-5 log, in order to file the item or to rectify lacking or incorrect information.

Fraction (1/4 1/4 1/4) Section-Township-Range changed:

listed as NE NE, 23-20S-1W

changed to SE NE NE, 23-27S-1W

Other changes: Initial statements: _____

Changed to: _____

Comments: _____

verification method: written & legal descriptions, city map, and

Wichita West 1:24,000 topo map. initials: DBL date: 10/24/2001

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726
to: Kansas Dept of Health & Environment Bureau of Water Industrial Programs, Bldg 283, Forbes Field, KS 66620

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County Sedgwick	Fraction 1/4 NE 1/4 NE 1/4	Section number 23	Township number T 20 S	Range number R 1W E/W
2. Distance and direction from nearest town or city: Street address of well location if in city: old 96 Hwy & West Street North,		3. Owner of well: Globe Paving & Construction Rt. or street: 200 West 10th Street City, state, zip code: Wichita, Kansas			
4. Locate with "X" in section below: N W E S 1 Mile		Sketch map: Wichita, Kansas		6. Bore hole dia. 11 in. Completion date 8-28-77 Well depth 47 ft.	
				7. ☒ Cable tool ☒ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☐ Bored ☐ Reverse rotary	
				8. Use: ☐ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Stock ☒ Lawn ☐ Oil field water ☐ Other	
				9. Casing: Material PVC Height: Above or below Threaded ☐ Welded ☐ Surface 12 in. RMP ☐ PVC ☒ Weight 3.96 lbs./ft. Dia. 6 in. to 47 ft. depth Wall Thickness: inches or Dia. ☐ in. to ☐ ft. depth gage No. .316	
5. Type and color of material		From	To	10. Screen: Manufacturer's name PVC NSF approved 200PSI	
Topsoil		0	3	Type PVC Dia. 6"	
Clay		3	10	Slot .06 Length 20'	
Fine Sand		10	20	Set between 27 ft. and 47 ft.	
Medium Sand		20	47	Gravel pack? yes Size range of material 1/4-1/8"	
				11. Static water level: 15 ft. below land surface Date 8-28-77	
				12. Pumping level below land surfaces: ft. after hrs. pumping g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield g.p.m.	
				13. Water sample submitted: yes mo./day/yr. Yes No Date	
				14. Well head completion: 12 capped Pitless adapter inches above grade	
				15. Well grouted? yes 1-2 fine sand mix With: Neat cement Bentonite ☒ Concrete Depth: From 40' ft. to 14 ft.	
				16. Nearest source of possible contamination: NONE ft. Direction Type Well disinfected upon completion? ☒ Yes No	
				17. Pump: ☒ Not installed Manufacturer's name Model number HP Volts Length of drop pipe ft. capacity g.p.m. Type: ☐ Submersible ☐ Turbine ☐ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other	
		(Use a second sheet if needed)			
18. Elevation:	19. Remarks: Flat Ground		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Harp Well & Pump 236 Business name Address Wichita, Kansas 67209 License No. Signed M. Arnold Date 12-1-77 Authorized representative		
Topography: ☐ Hill ☐ Slope ☐ Upland ☐ Valley	No apparent source for contamination. Pump not installed by our company.				

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5