


1 LOCATION OF WATER WELL: Fraction SW 1/4 Section Number 17 Township Number 27S Range Number 1E
 County: Sedgwick
 Distance and direction from nearest town or city street address of well if located within city? 028 N. Hoover

2 WATER WELL OWNER: Elmer & Glenda Dyck
 RR#, St. Address, Box #: 10100 W. Maple
 City, State, ZIP Code: Wichita, KS 67209
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 36 ft. ELEVATION: 10-29-01
 Depth(s) Groundwater Encountered 1. 10 ft. 2. 36 ft. 3. 10-29-01 ft.
 WELL'S STATIC WATER LEVEL 10 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 10 ft. after 10 hours pumping 10 gpm
 Est. Yield 20 gpm Well water was 36 ft. after 10 hours pumping 10 gpm
 Bore Hole Diameter 11 in. to 36 ft. and 36 in. to 36 ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 1 Steel 3 RMP (SR) Welded
 2 PVC 5 4 ABS Threaded
 7 Fiberglass
 Blank casing diameter 12 in. to 27 ft. Dia 2.40 in. to 160 psi
 Casing height above land surface 12 in. weight 2.40 lbs./ft. Wall thickness or gauge No. 160 psi
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 27 ft. to 36 ft. From 10 ft. to 36 ft.
 GRAVEL PACK INTERVALS: From 10 ft. to 36 ft. From 10 ft. to 36 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 10 ft. From 10 ft. to 36 ft. From 10 ft. to 36 ft.
 What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
 Direction from well? southwest How many feet? 60

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	top soil			
2	36	fine to med. sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-29-01 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 10-31-01
 under the business name of Weninger Drilling Inc. by (signature) Michelle E. Dyck

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.