

1] LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Sedgwick		SW 1/4 NW 1/4 NW 1/4		25		T 27 S		R 1 EW	
Distance and direction from nearest town or city street address of well if located within city? University & West Streets, Wichita KS									
2] WATER WELL OWNER: Coastal Mart									
RR#, St. Address, Box #: 909 Greenway Plaza									
City, State, ZIP Code: Houston, TX 77040									
Board of Agriculture, Division of Water Resources									
Application Number:									
3] LOCATE WELL'S LOCATION WITH 4] DEPTH OF COMPLETED WELL: 20.0 ft. ELEVATION:									
AN "X" IN SECTION BOX:		Depth(s) Groundwater Encountered 1. 16 ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 16.0 ft. below land surface measured on mo/day/yr 10-17-01							
Pump test data: Well water was ft. after hours pumping gpm									
Est. Yield gpm: Well water was ft. after hours pumping gpm									
Bore Hole Diameter: 8.5 in. to 20.0 ft. and in. to ft.									
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well									
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)									
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well									
Was a chemical/bacteriological sample submitted to Department? Yes. No. X; If yes, mo/day/yr sample was submitted									
Water Well Disinfected? Yes No X									
5] TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)									
2 PVC 4 ABS 7 Fiberglass									
Blank casing diameter in. to 10.0 ft. Dia in. to ft. Dia in. to ft.									
Casing height above land surface flush in. weight 70.2 lbs./ft. Wall thickness or gauge No. Sch. 40									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)									
12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 2 Mill slot 3 Gauzed wrapped 8 Saw cut 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes									
7 Torch cut 10 Other (specify) ft.									
SCREEN-PERFORATED INTERVALS: From 10.0 ft. to 20.0 ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 8.0 ft. to 20.0 ft. From ft. to ft.									
From ft. to ft. From ft. to ft.									
6] GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 2.0 ft. to 8.0 ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
13 Insecticide storage									
Direction from well? How many feet?									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 6 Clayey Sand									
6 20 Sand, Fining upwards									
7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-17-01 and this record is true to the best of my knowledge and belief. Kansas									
Water Well Contractor's Licence No. 531 This Water Well Record was completed on (mo/day/yr) 11-9-01									
under the business name of Geotechnical Services Inc. by (signature) [Signature]									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone 785-296-5524. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.									