

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Sedgwick		NE NE ¼ NE ¼ NE ¼		29		T 27 S		R 1 E/W	
Distance and direction from nearest town or city street address of well if located within city? 301 S. Tylor; Wichita, Kansas									
2 WATER WELL OWNER: Quiktrip Corporation									
RR#, St. Address, Box # : PO Box 3475					Board of Agriculture, Division of Water Resources				
City, State, ZIP Code : Tulsa, Oklahoma 74101					Application Number:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL : 40 ft. ELEVATION: 1330.99						
			Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.						
			WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr						
			Pump test data: Well water was NA ft. after hours pumping gpm						
			Est. Yield NA gpm: Well water was ft. after hours pumping gpm						
			Bore Hole Diameter 8 in. to 40 ft. and in. to ft.						
			WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well						
			1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)						
			2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well ✓ Air Sparge Well						
			Was a chemical/bacteriological sample submitted to Department? Yes.....No ✓ ; If yes, mo/day/yr sample ✓ was submitted						
			Water Well Disinfected? Yes No ✓						
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded									
2 ✓ PVC 4 ABS 7 Fiberglass Threaded. ✓									
Blank casing diameter 2 in. to 37.5 ft. Dia in. to ft. Dia in. to ft.									
Casing height above land surface -8.64 in. weight lbs./ft. Wall thickness or gauge No. SCH. 40									
TYPE OF SCREEN OR PERFORATION MATERIAL									
1 Steel 3 Stainless steel 5 Fiberglass 7 ✓ PVC 10 Asbestos-cement									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)									
12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 2 ✓ Mill slot 3 Gauzed wrapped 8 Saw cut 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes									
7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 37.5 ft. to 40 ft. From ft. to ft.									
From ft. to ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 0 ft. to 2.5 ft. From 24.5 ft. to 40 ft.									
From ft. to ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 ✓ Bentonite 4 Other									
Grout Intervals: From 2.5 ft. to 24.5 ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 ✓ Other (specify below)									
13 Insecticide storage Former Tank Basin									
Direction from well? N How many feet? 0									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 1 Concrete,									
1 4 Clay, Black									
4 9 Silt, Orange									
9 11 Silt, Orange									
11 17 Sand, Orange									
17 19 Sand, Orange Brown									
19 24 Sand, Brown									
24 40 Sand, Gray									
ASW1, Tag # 00344991, Flushmount									
Project Name: Quiktrip - Greenfield									
GeoCore # 722, KDHE # U2-087-1149									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction									
and was completed on (mo/day/year) 11/21/01 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 12/18/01									
under the business name of GeoCore Services, Inc. by (signature) <i>Dale Bell</i>									

OFFICE USE ONLY

T

R

EW

SEC

N

N

N