

SE SE SW NW

WATER WELL RECORD Form WWC-5 KSA 82a-1212 ID No.

1 LOCATION OF WATER WELL:		Fraction $\frac{1}{4}$ $\frac{1}{4}$ $\frac{1}{4}$ $\frac{1}{4}$		Section Number 4	Township Number 27 S	Range Number 1 E
County: Sedgewick						
Distance and direction from nearest town or city street address of well if located within city? 8406 North Ridge Ct.						
2 WATER WELL OWNER: Craig Stuart Homes		Board of Agriculture, Division of Water Resources				
RR#, St. Address, Box #: 2708 N. Lake Ridge		Application Number:				
City, State, ZIP Code: Winnetka, KS 67205-05						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 45 ft. 5 ELEVATION: 1230 ft.				
		Depth(s) Groundwater Encountered 1 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 45 ft. below land surface measured on mo/day/yr Pump test data: Well water was 70 gpm ft. after 11 hours pumping Est. Yield 70 gpm Well water was 95 ft. after 11 hours pumping Bore Hole Diameter 11 in. to 95 ft. and 11 in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well disposal 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes. No. X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No				
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped				
1 Steel 3 RMP (SR)		Welded				
2 PVC 4 ABS		Threaded				
Blank casing diameter 12 in. to 57 ft. Dia		Blank casing diameter 12 in. to 57 ft. Dia				
Casing height above land surface 12 in. weight 2.40 lbs./ft.		Casing height above land surface 12 in. weight 2.40 lbs./ft.				
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement				
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)				
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut 11 None (open hole)				
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		10 Other (specify)				
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)						
SCREEN-PERFORATED INTERVALS: From 57 ft. to 95 ft.		SCREEN-PERFORATED INTERVALS: From 57 ft. to 95 ft.				
GRAVEL PACK INTERVALS: From 45 ft. to 95 ft.		GRAVEL PACK INTERVALS: From 45 ft. to 95 ft.				
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other		Grout Intervals: From 3 ft. to 45 ft.				
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well				
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)				
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage		Direction from well? east How many feet? 15				
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
0	2	top soil				
2	20	clay				
20	65	fine sand				
65	95	fine to med sand				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-30-01 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 318 This Water Well Record was completed on (mo/day/yr) 12-12-01 under the business name of Weninger Drilling Inc. by (signature) Michelle Georges						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone 785-296-5524. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.						