

1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 NE 1/4 Section Number 20 Township Number 27 S Range Number 1 E W
County Sedgewick Distance and direction from nearest town or city street address of well if located within city? 304 N. Westfield

2 WATER WELL OWNER: Bulmarin 10652 Woodsmant Ct. Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : 10652 Woodsmant Ct. Application Number:
City, State, ZIP Code : Lawrence, KS 66034-66

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the center section, labeled NW, NE, SW, SE, and S. A scale bar indicates 1 mile.]

4 DEPTH OF COMPLETED WELL: 66 ft. ELEVATION: 2-25-02 ft.
Depth(s) Groundwater Encountered 15 ft. below land surface measured on mo/day/yr 2-25-02
WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr 2-25-02
Pump test data: Well water was 11 ft. after 66 hours pumping 25 gpm
Est. Yield 25 gpm: Well water was 11 ft. after 66 hours pumping 25 gpm
Bore Hole Diameter 11 in. to 66 ft., and 66 in. to 66 ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes. No. X; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued. X Clamped.
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
2 PVC 5 4 ABS 7 Fiberglass Threaded
Blank casing diameter 12 in. to 50 ft., Dia 2.40 in. to 66 ft., Dia 1600 psi
Casing height above land surface 12 in., weight 2.40 lbs./ft. Wall thickness or gauge No. 1600 psi
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 50 ft. to 66 ft., From 66 ft. to 66 ft.
GRAVEL PACK INTERVALS: From 15 ft. to 66 ft., From 66 ft. to 66 ft.

6 GROUT MATERIAL: 1 Neat cement 15 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 3 ft. to 15 ft., From 15 ft. to 66 ft., From 66 ft. to 66 ft.
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
Direction from well? north How many feet? 15

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-25-02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 318 This Water Well Record was completed on (mo/day/yr) 2-27-02 under the business name of WENNER DRILLING INC. by (signature) Michelle Gorges

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone 785-296-5524. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.