

WATER WELL RECORD

Form WWC-5

KSA 82a-1212 ID No.

t. 27 s.

1) LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		9 1/4 SE 1/4 NE 1/4	6	T 12N S	R 1 E
Distance and direction from nearest town or city street address of well if located within city?					
SU Yang Chan 11017 W st Sterling Wichita					
2) WATER WELL OWNER: SU Yang Chan					
RR#, St. Address, Box # : 11017 W st Sterling			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Wichita KS			Application Number:		
3) LOCATE WELL'S LOCATION WITH		4) DEPTH OF COMPLETED WELL: 60 ft. ELEVATION:			
AN "X" IN SECTION BOX:		Depth(s) Groundwater Encountered 1. 26 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 26 ft. below land surface measured on mo/day/yr 10-7-02			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 10 in. to 60 ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes. No. If yes, mo/day/yr sample was submitted			
5) TYPE OF BLANK CASING USED:		CASING JOINTS: Glued. Clamped.			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile			
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)			
Blank casing diameter 5 in. to 60 ft., Dia		7 Fiberglass			
Casing height above land surface 14 in., weight 160 lbs./ft.		Wall thickness or gauge No. 26			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7-PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		10 Other (specify) ft.			
2 Louvered shutter 4 Key punched 7 Torch cut					
SCREEN-PERFORATED INTERVALS: From 50 ft. to 60 ft.		ft. to ft.			
GRAVEL PACK INTERVALS: From 20 ft. to 60 ft.		ft. to ft.			
6) GROUT MATERIAL:		3 Bentonite 4 Other			
Grout Intervals: From 2 ft. to 20 ft.		ft. to ft.			
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard					
Direction from well? East		How many feet? 20			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top Soil			
2	21	clay			
21	26	fine sand			
26	60	med coarse sand			
7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-7-02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 611 This Water Well Record was completed on (mo/day/yr) 10-7-02 under the business name of Chase Drilling by (signature) [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone 785-296-5524. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.					