

WATER WELL RECORD

Form WWC-5

KSA 82a-1212 ID No.

1 LOCATION OF WATER WELL: Fraction 1/4 SW 1/4 SE 8 Section Number Township Number Range Number
Country Sedgwick KS Distance and direction from nearest town or city street address of well if located within city? 1400 Westfield St.
2 WATER WELL OWNER: Tretop Nursery
RR#, St. Address, Box #: 5910 E. 37th N.
City, State, ZIP Code: Wichita KS 67220
Board of Agriculture, Division of Water Resources
Application Number:
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:
4 DEPTH OF COMPLETED WELL: 81 ft. ELEVATION: 3-12-02
Depth(s) Groundwater Encountered: 18 ft. below land surface measured on mo/day/yr
WELL'S STATIC WATER LEVEL: 18 ft. below land surface measured on mo/day/yr
Pump test data: Well water was 25 gpm ft. after 81 hours pumping gpm
Est. Yield: 25 gpm Well water was 81 ft. after 81 hours pumping gpm
Bore Hole Diameter: 11 in. to 81 ft., and in. to ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes No
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
Blank casing diameter: 6 in. to 61 ft., Dia. 2.40 in. to 160 ft., Dia.
Casing height above land surface: 12 in., weight 2.40 lbs./ft. Wall thickness or gauge No. 160 ft.
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 61 ft. to 81 ft., From 81 ft. to ft.
GRAVEL PACK INTERVALS: From 18 ft. to 81 ft., From 81 ft. to ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 3 ft. to 18 ft., From 18 ft. to ft.
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
Direction from well? Northwest How many feet? 15
7 FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS
0 2 topsoil
2 12 fine to med sand
12 54 clay
54 65 sugar sand
65 80 med. sand
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-12-02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 318 This Water Well Record was completed on (mo/day/yr) 3-15-02 under the business name of Weninger Drilling Inc by (signature) Michelle Rode