

LOCATION OF WATER WELL:		FRACTION	SECTION NUMBER	TOWNSHIP NUMBER	RANGE NUMBER
Sedgwick		NW 1/4 NW 1/4 NE 1/4	7	T 27 S	R 1W E/W
Distance and direction from nearest town or city street address of well if located within city? 2103 N. Mars Wichita, Kansas					
WATER WELL OWNER: RR#,ST. ADDRESS,BOX # CITY, STATE:		HICKEY, Susan 2103 N. Mars Wichita, Kansas	Board of Agriculture, Division of Water Resource ZIP CODE: Application Number:		
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N NW NE SW SE S		DEPTH OF COMPLETED WELL: 65 ft. ELEVATION: Depth of groundwater Encountered: ft. WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 4/3/03 Pump test data: Well water was ft. after hours of pumping @ gpm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm Bore Hole Diameter 12 in. to 65 ft. and in. to ft. WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below) Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO			
TYPE OF CASING USED: Blank casing diameter Casing height above land surface: TYPE OF SCREEN OR PERFORATION MATERIAL: SCREEN OR PERFORATION OPENINGS ARE: GRAVEL PACK INTERVALS:		1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Threaded Clamped Welded 2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26 12 in., Weight: 2.35 lbs./ft. Wall thickness or gauge No. .214 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)			
		SCREEN - PERFORATION INTERVAL From 45 ft. to 65 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 24 ft. to 65 ft., From ft. to ft.			
GROUT MATERIALS: Neat cement Cement Grout Bentonite Other bentonite hole plug Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below) 3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage Direction from well? East How many feet? 75					
		LITHOLOGIC LOG From To topsoil clay fine sand medium sand			
Contractor's or Landowner's Certification: This water well was constructed reconstructed plugged under my jurisdiction and completed on (mo/day/year) 4-3-2003 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 4-7-2003 under the business name of Harp Well & Pump Service Inc. by (signature) Jedd S. Harp					