

1 LOCATION OF WATER WELL: County: <u>Saline</u> Fraction: <u>NW 1/4 NW 1/4 NE 1/4</u> Section Number: <u>19</u> Township Number: <u>T 27 S</u> Range Number: <u>R 1 E</u>	
Distance and direction from nearest town or city street address of well if located within city? <u>660 Park Dale</u>	
2 WATER WELL OWNER: <u>my Jackson</u> RR#, St. Address, Box #: <u>660, Park Dale</u> City, State, ZIP Code: <u>Wichita KS</u>	
Board of Agriculture, Division of Water Resources Application Number: <u>none</u>	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>40</u> ft. ELEVATION: <u>1300</u>
	Depth(s) Groundwater Encountered: <u>1 16</u> ft. 2 ft. 3 ft.
	WELL'S STATIC WATER LEVEL: <u>16</u> ft. below land surface measured on mo/day/yr <u>5-23-03</u>
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial <u>7</u> Domestic (lawn & garden) 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No <u>X</u>	
5 TYPE OF BLANK CASING USED:	
1 Steel <u>2</u> PVC Blank casing diameter <u>6</u> in. to <u>20</u> ft., Dia in. to ft., Dia in. to ft.	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass Casing height above land surface <u>12</u> in., weight lbs./ft. Wall thickness or gauge No. <u>160</u>
3 RMP (SR) 4 ABS	8 Concrete tile 9 Other (specify below) Casing joints: Glued <u>X</u> Clamped Welded Threaded
TYPE OF SCREEN OR PERFORATION MATERIAL:	
1 Steel 2 Brass 3 Stainless Steel 4 Galvanized Steel 5 Fiberglass 6 Concrete tile	<u>7</u> PVC 8 RMP (SR) 9 ABS 10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	
1 Continuous slot 2 Louvered shutter <u>3</u> Mill slot 4 Key punched	5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) ft. 11 None (open hole)
SCREEN-PERFORATED INTERVALS: From <u>20</u> ft. to <u>40</u> ft., From ft. to ft.	
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft.	
<u>none</u>	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other	
Grout Intervals: From <u>0</u> ft. to <u>16</u> ft., From ft. to ft., From ft. to ft.	
What is the nearest source of possible contamination:	
1 Septic tank 2 Sewer lines <u>3</u> Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit	7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)
Direction from well? <u>west</u> How many feet? <u>11</u>	
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS	
<u>0</u> <u>7</u>	<u>Top Soil</u>
<u>7</u> <u>20</u>	<u>Finest tan sand</u>
<u>20</u> <u>40</u>	<u>Coarse tan sand</u>
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>6-23-03</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No <u>473</u> This Water Well Record was completed on (mo/day/yr) <u>5-23-03</u> under the business name of <u>Beardley Pump & Well</u> by (signature) <u>David Beck</u>	
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.	