

1 LOCATION OF WATER WELL: Fraction NE 1/4 NE 1/4 SW 1/4 Section Number 14 Township Number T 27 S Range Number R 1W EW	
County: SEDGWICK Distance and direction from nearest town or city street address of well if located within city? backyard - 5 ft west of shed - 920 N. Bebe Wichita KS	
2 WATER WELL OWNER: TRAVES WARE 920 N. BEBE WICHITA KS 672 Board of Agriculture, Division of Water Resources Application Number: Unknown	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the center section (SE 1/4 of the NE 1/4)]	
4 DEPTH OF COMPLETED WELL: 20 ft. ELEVATION: 12 ft. below land surface measured on mo/day/yr	
WELL'S STATIC WATER LEVEL: Pump test data: Well water was 12 ft. after 12 hours pumping 12 gpm	
Est. Yield: 12 gpm: Well water was 12 ft. after 12 hours pumping 12 gpm	
Bore Hole Diameter: 12 in. to 12 ft., and 12 in. to 12 ft.	
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes. No. X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No	
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) CASING JOINTS: Glued. Clamped. 2 PVC 4 ABS 7 Fiberglass Threaded.	
Blank casing diameter: 4 in. to 4 ft., Dia. 4 in. to 4 ft., Dia. 4 in. to 4 ft.	
Casing height above land surface: 18 in., weight 18 lbs./ft. Wall thickness or gauge No. 18	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 6 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 9 ABS 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 6 Wire wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 7 Torch cut 9 Drilled holes 10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 12 ft. to 12 ft., From 12 ft. to 12 ft., From 12 ft. to 12 ft.	
GRAVEL PACK INTERVALS: From 12 ft. to 12 ft., From 12 ft. to 12 ft., From 12 ft. to 12 ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other	
Grout Intervals: From 12 ft. to 12 ft., From 12 ft. to 12 ft., From 12 ft. to 12 ft.	
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage NONE	
Direction from well? How many feet?	
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS	
• extend 15" to 18" above ground	
• pitless adaptor	
• pump	
• electrical	
• disinfect well	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/28/03 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 620 This Water Well Record was completed on (mo/day/yr) 6/28/03 under the business name of J.M. Enterprises by (signature) [Signature]	
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone 785-296-5524. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.	