

1	LOCATION OF WATER WELL: Sedgwick	FRACTION NE 1/4 NW 1/4 SE 1/4	SECTION NUMBER 5	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 1W E/W
---	--	---	----------------------------	----------------------------------	---------------------------------

2550 N. Bellwood Wichita, Kansas

Board of Agriculture, Division of Water Resource

ZIP CODE: _____ Application Numbers: _____

4. DEPTH OF COMPLETED WELL:		70	ft.	ELEVATION:			
Depth of groundwater Encountered:			ft.		ft.		ft.
WELL'S STATIC WATER LEVEL		30	FT. BELOW LAND SURFACE MEASURED ON	mo/day/yr:	9/12/03		
Pump test data:		Well water was		ft. after	hours of pumping @		gpm
Est. Yield:	gpm	Well water was		ft. after	hours of pumping @		gpm
Bore Hole Diameter	12	in.	to	70	ft.	and	in. to ft.
WELL WATER TO BE USED AS:					9. Dewatering	11. Injection well	
1. Domestic	3. Feedlot	5. Public water supply	7. Lawn and garden only			12. Other (Specify below)	
2. Irrigation	4. Industrial	6. Oil field water supply	8. Air conditioning			10. Monitoring well	
Was a chemical/bacteriological sample submitted to Department?			YES	NO	; If yes, what mo/day/yr was sample submitted		
			Was Water Well Disinfected?			YES	NO

Blank casing diameter **5** in. to **50** ft., Dia. in. to ft., Dia. in. to ft.

Casing height above land surface: **12** in., Weight: **2.35** lbs. / ft. Wall thickness or gauge No. **.214**

TYPE OF SCREEN OR PERFORATION MATERIAL:

1. Steel 3. Stainless Steel 5. Fiberglass **7. PVC** 9. ABS 11. Other (specify)

2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)

2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)

SCREEN - PERFORATION INTERVAL	From	50	ft.	to	70	ft.,	From	ft.	to	ft.
	From		ft.	to		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:	From	24	ft.	to	70	ft.,	From	ft.	to	ft.
	From		ft.	to		ft.,	From	ft.	to	ft.

6	GROUT MATERIALS:										
	1. Neat cement			2. Cement Grout			3. Bentonite			Other bentonite hole plug	
	Grout Intervals:		From 4 ft.	to 24 ft.,	From	ft.	to	ft.,	From	ft.	to
What is the nearest source of possible contamination:											
1. Septic tank		4. Lateral lines		7. Pit privy		10. Livestock pens		13. Insecticide storage		15. Oil well/Gas well	
2. Sewer lines		5. Cess Pool		8. Sewage lagoon		11. Fuel storage		14. Abandon water well		16. Other (specify below)	
3. Watertight sewer line		6. Seepage pit		9. Feed yard		12. Fertilizer storage					
Direction from well? East								How many feet? 90			

[illegible]

7 Contractor's or Landowner's Certification: This water well was 1. **constructed** 2. **reconstructed** or 3. **plugged** under my jurisdiction and was completed on (mo/day/year) **9/12/2003** and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. **236** This water well record was completed on (mo/day/year) **9/15/2003**

under the business name of **Harp Well & Pump Service Inc.** by (signature) *[Signature]*