


NW SE NW NW

WATER WELL RECORD

Form WWC-5

KSA 82a-1212

ID No.

1 LOCATION OF WATER WELL: Fraction 1/4 1/4 1/4 1/4 Section Number 6 Township Number T 270 S Range Number R 1 E/W	
Distance and direction from nearest town or city street address of well if located within city? 1711 Ryan Place	
2 WATER WELL OWNER: Brandon Adams	
RR#, St. Address, Box # : City, State, ZIP Code : Board of Agriculture, Division of Water Resources Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 60 ft. ELEVATION: 25-04 ft.
	Depth(s) Groundwater Encountered 24 ft. 2 ft. WELL'S STATIC WATER LEVEL 24 ft. below land surface measured on mo/day/yr 25-04 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 25 gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No	
5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 5 4 ABS 7 Fiberglass Threaded Blank casing diameter 5 in. to 50 ft., Dia 2.48 in. to 160 ft., Dia Casing height above land surface 12 in., weight 2.48 lbs./ft. Wall thickness or gauge No. 160 ps TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-Cement 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify) 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft. SCREEN-PERFORATED INTERVALS: From 50 ft. to 60 ft., From 60 ft. to ft. GRAVEL PACK INTERVALS: From 24 ft. to 100 ft., From 100 ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 3 ft. to 24 ft., From 24 ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? How many feet?	
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS	
0 3 topsoil	
3 24 clay	
24 60 med sand	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-25-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 378 This Water Well Record was completed on (mo/day/yr) 2-25-04 under the business name of Welinger Drilling Inc. by (signature) Michael Crooks	
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.	