

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		SW 1/4 NW 1/4 NE 1/4	5	T 27S S	R 1W EW
Distance and direction from nearest town or city street address of well if located within city?					
9409 Ryan Ct.; Wichita					
2 WATER WELL OWNER: T.J. Thomas					
RR#, St. Address, Box #: 9409 Ryan Ct.					
City, State, ZIP Code: Wichita, KS					
Board of Agriculture, Division of Water Resources					
Application Number:					
3 LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL: 0.5 ft. ELEVATION:					
AN "X" IN SECTION BOX:		Depth(s) Groundwater Encountered 1. 19 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 19 ft. below land surface measured on mo/day/yr 2-24-04			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 10 in. to 6.5 ft. and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial Domestic (lawn & garden) 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes X No					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
			7 Fiberglass		Threaded
Blank casing diameter 5 in. to 6.5 ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface 16 in. weight 160 lbs./ft. Wall thickness or gauge No. 26					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
				9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	ft.
SCREEN-PERFORATED INTERVALS: From 55 ft. to 65 ft. From ft. to ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 24 ft. to 65 ft. From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 2 ft. to 24 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
13 Insecticide storage					
Direction from well? North					
How many feet? 40					
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0 2 topsoil					
2 22 clay					
22 26 fine sand / clay					
26 31 fine sand					
31 42 med sand					
42 65 coarse / med sand					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-24-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 11111 This Water Well Record was completed on (mo/day/yr) 2-24-04 under the business name of Chase Drilling by (signature) Rick Chase					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone 785-296-5524. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.					