


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Sedgwick		FRACTION: SE 1/4 SE 1/4 NE 1/4		SECTION NUMBER: 21		TOWNSHIP NUMBER: T 27 S		RANGE NUMBER: R 1W E/W	
Distance and direction from nearest town or city street address of well if located within city?									
411 Acadia Wichita, Kansas									
2 WATER WELL OWNER: OWEN, Judy		Board of Agriculture, Division of Water Resource							
RR#, ST. ADDRESS, BOX #: 411 Acadia		CITY, STATE: Wichita, Kansas		ZIP CODE:		Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION:							
1 Mile N W E S		Depth of groundwater Encountered: ft. ft. ft.							
		WELL'S STATIC WATER LEVEL 25 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 3/29/04							
		Pump test data: Well water was ft. after hours of pumping @ gpm							
		Est. Yield: gpm Well water was ft. after hours of pumping @ gpm							
		Bore Hole Diameter 12 in. to 60 ft. and in. to ft.							
WELL WATER TO BE USED AS:		9. Dewatering 11. Injection well							
1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below)									
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well									
Was a chemical/bacteriological sample submitted to Department?		YES NO If yes, what mo/day/yr was sample submitted							
5 TYPE OF CASING USED:		CASING JOINTS: Glued Threaded							
1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below)		Welded Clamped							
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26									
Blank casing diameter 5 in. to 40 ft., Dia. in. to ft., Dia. in. to ft.									
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214									
TYPE OF SCREEN OR PERFORATION MATERIAL:		11. Other (specify)							
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 12. None used (open hole)									
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement									
SCREEN OR PERFORATION OPENINGS ARE:		11. None (open hole)							
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes		10. Other (specify)							
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut									
SCREEN - PERFORATION INTERVAL From 40 ft. to 60 ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From 24 ft. to 60 ft., From ft. to ft.									
6 GROUT MATERIALS:		Other bentonite hole plug							
1. Neat cement 2. Cement Grout 3. Bentonite									
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.									
What is the nearest source of possible contamination:		15. Oil well/Gas well							
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage		16. Other (specify below)							
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well									
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage									
Direction from well? West		How many feet? 95							
From To LITHOLOGIC LOG From To LITHOLOGIC LOG									
0 4 topsoil									
4 20 sandy clay									
20 30 fine sand									
30 35 clay									
35 60 medium coarse sand									
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 3/29/2004 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 3/31/2004									
under the business name of Harp Well & Pump Service Inc. by (signature) J. d. S. Harp									