

1 LOCATION OF WATER WELL: Fraction 1/4 1/4 1/4 1/4 Section Number 6 Township Number T 27 S Range Number R 1 EW

County: Sedgwick Distance and direction from nearest town or city street address of well if located within city: 1014 Ryan Circle - Wichita

2 WATER WELL OWNER: Mike & Sherrie Elders Board of Agriculture, Division of Water Resources Application Number: 4-12-04

RR#, St. Address, Box #: 2301 N. Cedarcrest Drive City, State, ZIP Code: Wichita, KS 67223

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 3x3 grid with 'X' in the SW section]

4 DEPTH OF COMPLETED WELL: 5 ft. ELEVATION: 4-12-04

Depth(s) Groundwater Encountered: 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL: 1 ft. below land surface measured on mo/day/yr 4-12-04

Est. Yield: 20 gpm test data: Well water was 1 ft. after 4 hours pumping 4 gpm

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded

Blank casing diameter 12 in. to 41 ft., Dia 240 in. to 1600 ft., Dia

Casing height above land surface 12 in., weight 240 lbs./ft. Wall thickness or gauge No. 1600

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Mill slot 3 Louvered shutter 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 11 None (open hole)

SCREEN-PERFORATED INTERVALS: From 4 ft. to 51 ft., From 51 ft. to 51 ft., From 51 ft. to 51 ft., From 51 ft. to 51 ft.

GRAVEL PACK INTERVALS: From 4 ft. to 51 ft., From 51 ft. to 51 ft., From 51 ft. to 51 ft., From 51 ft. to 51 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 40 ft., From 40 ft. to 40 ft., From 40 ft. to 40 ft., From 40 ft. to 40 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

Direction from well? north How many feet? 40

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 3 topsoil

3 18 clay

18 51 sand

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-12-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 318 This Water Well Record was completed on (mo/day/yr) 4-12-04 under the business name of Welling Drilling Inc by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.