

1 LOCATION OF WATER WELL: NE Fraction NW NE		Section Number 7	Township Number T 27 S	Range Number R 1 E	
County: Sedgwick					
Distance and direction from nearest town or city street address of well if located within city? 2030 Stoney Point					
2 WATER WELL OWNER: Ben Dhisenard					
RR#, St. Address, Box # : City, State, ZIP Code :			Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 51 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 12 ft. 2 ft. WELL'S STATIC WATER LEVEL 12 ft. below land surface measured on mo/day/yr 6-15-04 Pump test data: Well water was 20 gpm Well water was 12 ft. after 10 hours pumping 10 gpm Est. Yield 20 gpm Well water was 12 ft. after 10 hours pumping 10 gpm WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 9 Dewatering 12 Other (Specify below) 0 Domestic (lawn & garden) 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued X Clamped	
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)		Welded	
Blank casing diameter 12 in. to 41 ft. Dia 24 in. to 160 ft. Dia		Threaded			
Casing height above land surface 12 in. weight 240 lbs./ft. Wall thickness or gauge No. 160 ps					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR)		10 Asbestos-Cement			
2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS		11 Other (Specify)			
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 8 Mill slot 5 Guazed wrapped 8 Saw cut 11 None (open hole)		6 Wire wrapped 9 Drilled holes			
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)		ft.			
SCREEN-PERFORATED INTERVALS: From 41 ft. to 51 ft. From 12 ft. to 51 ft.					
GRAVEL PACK INTERVALS: From 12 ft. to 51 ft. From 12 ft. to 51 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 3 ft. to 12 ft. From 12 ft. to 48 ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well		11 Fuel storage 15 Oil well/Gas well			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)		13 Insecticide storage			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard		How many feet? 48			
Direction from well? east					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	topsoil			
2	17	clay			
17	25	fine sand			
25	51	gravel			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-15-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 318 This Water Well Record was completed on (mo/day/yr) 6-15-04 under the business name of Weninger Drilling Inc. by (signature) Richard Gork					