

1 LOCATION OF WATER WELL		Fraction		Section Number		Township Number		Range Number	
County: Sedgwick NE 1/4 NW 1/4 SW 1/4		9		T 27 S		R 1 E		10	
Distance and direction from nearest town or city street address of well if located within city limits									
2 WATER WELL OWNER: Dan Steckmeyer									
RR#, St. Address, Box # City, State, ZIP Code					Board of Agriculture, Division of Water Resources Application Number:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL 51 ft. ELEVATION: 17-2004						
			Depth(s) Groundwater Encountered 1 12 ft. 2 WELL'S STATIC WATER LEVEL 12 ft. below land surface measured on mo/day/yr Pump test data: Well water was 30 gpm. Well water was 30 ft. after 30 hours pumping 30 gpm. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well						
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No									
5 TYPE OF BLANK CASING USED:									
1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued X Clamped Welded Threaded									
Blank casing diameter 5 in. to 4 ft. Dia 24 in. to 160 ft. Dia									
Casing height above land surface 12 in., weight 240 lbs./ft. Wall thickness or gauge No. 160 ft.									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 2 Brass 3 Stainless Steel 4 Galvanized Steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)									
SCREEN-PERFORATED INTERVALS: From 41 ft. to 51 ft. From 12 ft. to 51 ft.									
GRAVEL PACK INTERVALS: From 12 ft. to 51 ft. From 12 ft. to 51 ft.									
6 GROUT MATERIAL:									
1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 3 ft. to 12 ft. From 12 ft. to 51 ft. From 12 ft. to 51 ft.									
What is the nearest source of possible contamination:									
1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)									
Direction from well? 45 East									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 1 topsoil									
1 25 clay									
25 35 fine sand									
35 40 clay									
40 5 med sand									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-20-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 38 This Water Well Record was completed on (mo/day/yr) 7-22-04 under the business name of Wenter Drilling by signature Oliver Edgar									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.									