

1 LOCATION OF WATER WELL	Fraction	Section Number	Township Number	Range Number
County: Sedgwick	SE 1/4 SW 1/4 SE 1/4	8	T 270 S	R 1 E

Distance and direction from nearest town or city street address of well if located within city limits: 2148 Winfield St.

2 WATER WELL OWNER: Stan Diskin	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : City, State, ZIP Code :	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 57 ft. ELEVATION:
	Depth(s) Groundwater Encountered 28 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 28 ft. below land surface measured on mo/day/yr 8-13-04 Pump test data: Well water was 30 gpm. Well water was 30 ft. after 30 hours pumping 30 gpm Est. Yield 30 gpm. Well water was 30 ft. after 30 hours pumping 30 gpm WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC	7 Fiberglass		Threaded
3 RMP (SR)			
4 ABS			
Blank casing diameter 12 in. to 12 ft. Dia 2.40 in. to 1600 ft. Dia			
Casing height above land surface 12 in., weight 2.40 lbs./ft. Wall thickness or gauge No. 1600PS			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-Cement	
1 Steel	8 RMP (SR)	11 Other (Specify)	
2 Brass	9 ABS	12 None used (open hole)	
3 Stainless Steel			
4 Galvanized Steel			
5 Fiberglass			
6 Concrete tile			
SCREEN OR PERFORATION OPENINGS ARE:	5 Guazed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
3 Mill slot			
4 Key punched			
SCREEN-PERFORATED INTERVALS: From 47 ft. to 57 ft.			
GRAVEL PACK INTERVALS: From 28 ft. to 57 ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
GROUT INTERVALS: From 3 ft. to 28 ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	14 Abandoned water well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	15 Oil well/Gas well
Direction from well? north			13 Insecticide storage	16 Other (specify below)
			How many feet? 40	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	topsoil			
3	10	fine sand			
10	20	clay			
20	36	med sand			
36	38	clay			
38	57	med sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-13-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 318 This Water Well Record was completed on (mo/day/yr) 8-13-04 under the business name of Wininger Drilling Inc. by (signature) Michelle Gurey
