

ID No.

LOCATION OF WATER WELL: Sedgwick County, NE 1/4, Sec 8, T 27S, R 1W, E/W

Distance and direction from nearest town or city street address of well if located within city? 11012 Greenspoint; Wichita

WATER WELL OWNER: Joe Herridge

R#, St. Address, Box #: 11012 Greenspoint, Wichita, KS

Board of Agriculture, Division of Water Resources, Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing section 16 with an 'X' in the center]

DEPTH OF COMPLETED WELL: 60 ft. ELEVATION: 1112.04 ft.

Depth(s) Groundwater Encountered: 17 ft. 2

WELL'S STATIC WATER LEVEL: 17 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 17 ft. after hours pumping gpm

Est. Yield: gpm: Well water was 17 ft. after hours pumping gpm

WELL WATER TO BE USED AS: 5 Public water supply, 8 Air conditioning, 11 Injection well, 1 Domestic, 3 Feedlot, 6 Oil field water supply, 9 Dewatering, 12 Other (Specify below), 2 Irrigation, 4 Industrial, 7 Domestic (lawn & garden), 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

TYPE OF BLANK CASING USED: 1 Steel, 2 PVC, 3 RMP (SR), 4 ABS, 5 Wrought iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below), CASING JOINTS: Glued X, Clamped, Welded, Threaded

Blank casing diameter: 5 in. to 60 ft., Dia. 160 in. to ft., Dia. 26 in. to ft.

Casing height above land surface: 10 in., weight 160 lbs./ft. Wall thickness or gauge No. 26

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Stainless Steel, 4 Galvanized Steel, 5 Fiberglass, 6 Concrete tile, 7 PVC, 8 RMP (SR), 9 ABS, 10 Asbestos-Cement, 11 Other (Specify), 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 2 Louvered shutter, 3 Mill slot, 4 Key punched, 5 Guazed wrapped, 6 Wire wrapped, 7 Torch cut, 8 Saw cut, 9 Drilled holes, 10 Other (specify), 11 None (open hole)

SCREEN-PERFORATED INTERVALS: From 50 ft. to 60 ft., From ft. to ft., From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 24 ft. to 60 ft., From ft. to ft., From ft. to ft., From ft. to ft.

GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other

Grout intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination: 1 Septic tank, 2 Sewer lines, 3 Watertight sewer lines, 4 Lateral lines, 5 Cess pool, 6 Seepage pit, 7 Pit privy, 8 Sewage lagoon, 9 Feedyard, 10 Livestock pens, 11 Fuel storage, 12 Fertilizer storage, 13 Insecticide storage, 14 Abandoned water well, 15 Oil well/Gas well, 16 Other (specify below)

Direction from well? East

How many feet? 17

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 2 topsoil

2 17 brown clay

17 31 fine silty sand

31 37 brown clay

37 43 med sand

43 44 tan clay

44 60 med to coarse sand + gravel

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/12/04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 11111 This Water Well Record was completed on (mo/day/yr) 11/13/05 by (signature) R Chase

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.