

1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction: $\frac{1}{4}$ NW $\frac{1}{4}$ NE $\frac{1}{4}$ NE	Section Number: 4	Township Number: T 27 S	Range Number: R 1 E W																																																																																																						
Distance and direction from nearest town or city street address of well if located within city? 2906 FOSSIL RIM WICHITA, KS																																																																																																											
2 WATER WELL OWNER: Cheryl Griffith RR#, St. Address, Box # : 2906 FOSSIL RIM City, State, ZIP Code : Wichita, KS, 67203 Board of Agriculture, Division of Water Resources Application Number:																																																																																																											
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 80 ft. ELEVATION:																																																																																																									
		Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 20 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield 25 gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well																																																																																																									
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No																																																																																																									
		5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded																																																																																																									
		Blank casing diameter 5 in. to 6.5 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 12 in., weight 2.40 lbs./ft. Wall thickness or gauge No. 140 P.H. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 PVC 10 Asbestos-Cement 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify) 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole)																																																																																																									
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft. SCREEN-PERFORATED INTERVALS: From 65 ft. to 80 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 80 ft. to 80 ft., From ft. to ft.																																																																																																											
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 3 ft. to 20 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? W How many feet? 250'																																																																																																											
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>1</td> <td>TOP SOIL</td> <td></td> <td></td> <td></td> </tr> <tr> <td>1</td> <td>10</td> <td>CLAY</td> <td></td> <td></td> <td></td> </tr> <tr> <td>10</td> <td>20</td> <td>FINE SAND</td> <td></td> <td></td> <td></td> </tr> <tr> <td>20</td> <td>40</td> <td>MED. SAND</td> <td></td> <td></td> <td></td> </tr> <tr> <td>40</td> <td>42</td> <td>CLAY</td> <td></td> <td></td> <td></td> </tr> <tr> <td>42</td> <td>60</td> <td>FINE SAND</td> <td></td> <td></td> <td></td> </tr> <tr> <td>60</td> <td>80</td> <td>MED. SAND</td> <td></td> <td></td> <td></td> </tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> <tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr> </tbody> </table>						FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	1	TOP SOIL				1	10	CLAY				10	20	FINE SAND				20	40	MED. SAND				40	42	CLAY				42	60	FINE SAND				60	80	MED. SAND																																																									
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																																																																						
0	1	TOP SOIL																																																																																																									
1	10	CLAY																																																																																																									
10	20	FINE SAND																																																																																																									
20	40	MED. SAND																																																																																																									
40	42	CLAY																																																																																																									
42	60	FINE SAND																																																																																																									
60	80	MED. SAND																																																																																																									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-21-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 740 This Water Well Record was completed on (mo/day/yr) 6-21-05 under the business name of WENINGER DRILLING INC. by (signature)																																																																																																											
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.																																																																																																											