

1 LOCATION OF WATER WELL: County: <u>SEDGWICK</u> Fraction: <u>1/4 NW 1/4</u> Section Number: <u>1</u> Township Number: <u>T 27 S</u> Range Number: <u>R 1 E</u>
--

Distance and direction from nearest town or city street address of well if located within city?

2630 N. BULLINGER WICHITA, KS 67204

2 WATER WELL OWNER: <u>DAVE OSBOURNE</u> RR#, St. Address, Box # : <u>2630 N. BULLINGER</u> City, State, ZIP Code : <u>WICHITA, KS, 67204</u>	Board of Agriculture, Division of Water Resources Application Number:
---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL <u>50</u> ft. ELEVATION:
--	--

Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL 12 ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 30 gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	5 Public water supply	8 Air conditioning	11 Injection well
2 Irrigation	4 Industrial	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
		7 Domestic (lawn & garden)	10 Monitoring well	

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes (X) No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC	7 Fiberglass		Threaded
3 RMP (SR)			
4 ABS			
Blank casing diameter <u>5 1/2</u> in. to <u>40</u> ft., Dia			
Casing height above land surface <u>12</u> in., weight <u>2-40</u> lbs./ft. Wall thickness or gauge No. <u>160</u> <u>RF</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Wrought iron	8 RMP (SR)	10 Asbestos-Cement
1 Steel	6 Concrete tile	9 ABS	11 Other (Specify)
2 Brass			12 None used (open hole)
3 Stainless Steel			
4 Galvanized Steel			
SCREEN OR PERFORATION OPENINGS ARE:	5 Guazed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	ft.
3 Mill slot			
4 Key punched			
SCREEN-PERFORATED INTERVALS:	From <u>40</u> ft. to <u>50</u> ft.	From ft. to ft.	
	From ft. to ft.	From ft. to ft.	
GRAVEL PACK INTERVALS:	From <u>20</u> ft. to <u>50</u> ft.	From ft. to ft.	
	From ft. to ft.	From ft. to ft.	

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From <u>3</u> ft. to <u>20</u> ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well? <u>WEST</u>				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)
				How many feet? <u>25</u>

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	TOP SOIL			
1	3	CLAY			
3	10	FINE SAND			
10	20	MEDIUM SAND			
20	35	FINE SAND			
35	50	GRAVEL			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>7-21-95</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No <u>740</u> This Water Well Record was completed on (mo/day/yr) <u>8-12-95</u> under the business name of <u>WENINGER DRILLING INC.</u> by (signature) <u>[Signature]</u>
