

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sedgewick</u>		<u>NW 1/4 SE 1/4 SW 1/4</u>	<u>23</u>	T <u>27</u> S	R <u>1</u> EW <u>(E)</u>
Distance and direction from nearest town or city street address of well if located within city? <u>201 South Doris</u>					
2 WATER WELL OWNER: <u>Colleen Edgmon</u>					
RR#, St. Address, Box # : <u>201 South Doris</u>				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code : <u>Winchester, KS 67209</u>				Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>40</u> ft. ELEVATION: <u>13</u> ft.			
		Depth(s) Groundwater Encountered <u>13</u> ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL <u>13</u> ft. below land surface measured on mo/day/yr <u>9-19-05</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield <u>25</u> gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial <u>(7) Domestic (lawn & garden)</u> 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No			
		5 TYPE OF BLANK CASING USED:			
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped <u>(2) PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <u>5</u> in. to <u>30</u> ft., Dia <u>2.5</u> in. to ft., Dia in. to ft. Casing height above land surface <u>12</u> in., weight lbs./ft. Wall thickness or gauge No. <u>30R26</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Guazed wrapped 6 Wire wrapped 7 Torch cut 8 RMP (SR) 9 ABS 11 None (open hole)			
SCREEN-PERFORATED INTERVALS:		10 Drilled holes 11 Other (specify) ft.			
GRAVEL PACK INTERVALS:		12 None used (open hole)			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout <u>(3) Bentonite</u> 4 Other					
Grout Intervals: From <u>3</u> ft. to <u>20</u> ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well <u>(2) Sewer lines</u> 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? <u>South West</u> How many feet? <u>40</u>					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>2</u>	<u>Topsoil</u>			
<u>2</u>	<u>10</u>	<u>Fine Sand</u>			
<u>10</u>	<u>17</u>	<u>Medium Sand</u>			
<u>17</u>	<u>19</u>	<u>Tan Clay</u>			
<u>19</u>	<u>40</u>	<u>Medium to Coarse Sand to Medium Gravel</u>			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>9-19-05</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No <u>238</u> This Water Well Record was completed on (mo/day/yr) <u>9-19-05</u> under the business name of <u>Wenger Irrigation</u> by (signature) <u>City Wenger</u>					