

1 LOCATION OF WATER WELL: Sedgwick		FRACTION NW 1/4 SW 1/4 NW 1/4	SECTION NUMBER 15	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 1W E/W																																																																																																																														
Distance and direction from nearest town or city street address of well if located within city? 1121 Summit Lawn Wichita, Kansas																																																																																																																																			
2 WATER WELL OWNER: RR#,ST. ADDRESS,BOX #: CITY, STATE:		MOONEY, Richard 1121 Summit Lawn Wichita, Kansas																																																																																																																																	
		ZIP CODE:		Application Number:																																																																																																																															
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N +---+ X +---+ S W E		4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION: Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL 25 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 9/20/05 Pump test data: Well water was ft. after hours of pumping @ gpm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm Bore Hole Diameter 12 in. to 60 ft. and in. to ft. WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply <u>7. Lawn and garden only</u> 9. Dewatering 11. Injection well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below) Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO																																																																																																																																	
5 TYPE OF CASING USED: 1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: <u>Glued</u> Threaded <u>2. PVC</u> 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26 Welded Clamped Blank casing diameter 5 in. to 40 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass <u>7. PVC</u> 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped <u>8. Saw cut</u> 10. Other (specify) SCREEN - PERFORATION INTERVAL From 40 ft. to 60 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 24 ft. to 60 ft., From ft. to ft.																																																																																																																																			
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug Grout intervals: From 4 ft. to 24 ft., From 35 ft. to 38 ft., From ft. to ft. What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below) <u>3. Watertight sewer line</u> 6. Seepage pit 9. Feed yard 12. Fertilizer storage Direction from well? East How many feet? 50 ft. plus																																																																																																																																			
<table border="1" style="width:100%; border-collapse: collapse;"><thead><tr><th colspan="3">LITHOLOGIC LOG</th><th colspan="3">LITHOLOGIC LOG</th></tr><tr><th>From</th><th>To</th><th></th><th>From</th><th>To</th><th></th></tr></thead><tbody><tr><td>0</td><td>4</td><td>topsoil</td><td></td><td></td><td></td></tr><tr><td>4</td><td>15</td><td>clay</td><td></td><td></td><td></td></tr><tr><td>15</td><td>25</td><td>fine sand</td><td></td><td></td><td></td></tr><tr><td>25</td><td>35</td><td>coarse sand</td><td></td><td></td><td></td></tr><tr><td>35</td><td>38</td><td>clay</td><td></td><td></td><td></td></tr><tr><td>38</td><td>60</td><td>medium coarse sand</td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr></tbody></table>						LITHOLOGIC LOG			LITHOLOGIC LOG			From	To		From	To		0	4	topsoil				4	15	clay				15	25	fine sand				25	35	coarse sand				35	38	clay				38	60	medium coarse sand																																																																																	
LITHOLOGIC LOG			LITHOLOGIC LOG																																																																																																																																
From	To		From	To																																																																																																																															
0	4	topsoil																																																																																																																																	
4	15	clay																																																																																																																																	
15	25	fine sand																																																																																																																																	
25	35	coarse sand																																																																																																																																	
35	38	clay																																																																																																																																	
38	60	medium coarse sand																																																																																																																																	
7 Contractor's or Landowner's Certification: This water well was 1. <u>constructed</u> 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 9-20-2005 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 9-23-2005 under the business name of Harp Well & Pump Service Inc. by (signature) <i>Jedd S. Harp</i>																																																																																																																																			