

1	LOCATION OF WATER WELL: Sedgwick	FRACTION SE 1/4 NW 1/4 SE 1/4	SECTION NUMBER 20	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 1W E/W
---	--	---	-----------------------------	----------------------------------	---------------------------------

9113 W. Douglas		Wichita, Kansas	
2	WATER WELL OWNER:	KLAUSMEYER CONSTRUCTION	
	RR#,ST. ADDRESS,BOX #:	10008 W. York	
	CITY, STATE:	Wichita, Kansas	Board of Agriculture, Division of Water Resources
		ZIP CODE:	Application Number:

4 DEPTH OF COMPLETED WELL: 98 ft. ELEVATION:

Depth of groundwater Encountered: ft.

WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 1/17/06

Pump test data: Well water was ft. after hours of pumping @ gpm

Est. Yield: gpm Well water was ft. after hours of pumping @ gpm

Bore Hole Diameter 12 in. to 98 ft. and in. to ft.

WELL WATER TO BE USED AS:

1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well

2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO

5 TYPE OF CASING USED:		9. Other (Specify below)		CASING JOINTS:		Threaded	
1. Steel	3. RPM (SR)	7. Fiberglass			<u>Glued</u>	Welded	Clamped
<u>2. PVC</u>	4. ABS	8. Concrete tile	SDR-26				
Blank casing diameter		5 in.	to	78 ft.,	Dia.	in.	to
Casing height above land surface:		12 in.,	Weight:	2.35 lbs. / ft.	Wall thickness or gauge No.	.214	
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1. Steel	3. Stainless Steel	5. Fiberglass	<u>7. PVC</u>	9. ABS	11. Other (specify)		
2. Brass	4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. Asbestos-Cement	12. None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:							
1. Continuous slot	3. Mill slot	5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)		
2. Louvered shutter	4. Key punched	6. Wire wrapped	<u>8. Saw cut</u>	10. Other (specify)			
SCREEN - PERFORATION INTERVAL	From	78 ft.	to	98 ft.,	From	ft.	to
	From	ft.	to	ft.,	From	ft.	to
GRAVEL PACK INTERVALS:	From	24 ft.	to	98 ft.,	From	ft.	to
	From	ft.	to	ft.,	From	ft.	to

6	GROUT MATERIALS:										
	1. Neat cement		2. Cement Grout		3. Bentonite		Other bentonite hole plug				
	Grout Intervals:	From 4 ft.	to 24 ft.	From	ft.	to	ft.,	From	ft.	to	ft.
	What is the nearest source of possible contamination:										
	1. Septic tank	4. Lateral lines	7. Pit privy	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well					
	2. Sewer lines	5. Cess Pool	8. Sewage lagoon	11. Fuel storage	14. Abandon water well	16. Other (specify below)					
	3. Watertight sewer line	6. Seepage pit	9. Feed yard	12. Fertilizer storage							
	Direction from well? West			How many feet? 50 feet plus							

[illegible]

To d d S. Harp