

LOCATION OF WATER WELL:		FRACTION	SECTION NUMBER	TOWNSHIP NUMBER	RANGE NUMBER
Sedgwick		NW 1/4 SE 1/4 NE 1/4	2	T 27 S	R 1W E/W
Distance and direction from nearest town or city street address of well if located within city?					
25th St. N. and West St. on West side Wichita, Kansas (6 logs on 1 permit)					
WATER WELL OWNER:		WICHITA, CITY OF			
RR#,ST. ADDRESS,BOX #:		455 N. Main Board of Agriculture, Division of Water Resource			
CITY, STATE:		Wichita, Kansas ZIP CODE: Application Number: 20060190			
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		DEPTH OF COMPLETED WELL: 48 ft. ELEVATION:			
1 Mile W E N S		Depth of groundwater Encountered: ft. WELL'S STATIC WATER LEVEL 15 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 7/11/06 Pump test data: Well water was ft. after hours of pumping @ gpm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm Bore Hole Diameter 12 in. to 48 ft. and in. to ft. WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below) Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO			
TYPE OF CASING USED:		CASING JOINTS:			
1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) Glued Threaded		Welded Clamped			
Blank casing diameter 8 in. to 20 ft., Dia. in. to ft., Dia. in. to ft.		SDR-26			
Casing height above land surface: 12 in., Weight: 5.52 lbs. / ft. Wall thickness or gauge No. .332					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)					
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)					
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)					
SCREEN - PERFORATION INTERVAL From 20 ft. to 36 ft., From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 20 ft. to 48 ft., From ft. to ft., From ft. to ft.					
GROUT MATERIALS:		Other bentonite hole plug			
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well					
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)					
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage		None Apparent			
Direction from well?		How many feet?			
From To LITHOLOGIC LOG		From To LITHOLOGIC LOG			
0	3	topsoil			
3	12	clay			
12	31	fine sand			
31	48	medium sand			
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 7/11/2006 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 236			This water well record was completed on (mo/day/year) 7/14/2006		
under the business name of Harp Well and Pump Service			by (signature) J o d d S. H a r p		