

1 LOCATION OF WATER WELL: Sedgwick		FRACTION SE 1/4 NW 1/4 NE 1/4	SECTION NUMBER 2	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 1W E/W
Distance and direction from nearest town or city street address of well if located within city? 25th St. N. and West St., 1/4 mile West (Emerald Bay) (5 plugs on 1 permit) Wichita, Kansas					
2	WATER WELL OWNER: WICHITA, CITY OF RR#,ST. ADDRESS,BOX #: 455 N. Main CITY, STATE: Wichita, Kansas		Board of Agriculture, Division of Water Resource ZIP CODE: Application Number: 20060422		
3	LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 50 ft. ELEVATION:		
1 Mile		Depth of groundwater Encountered: _____ ft.			
		WELL'S STATIC WATER LEVEL 15 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 3/7/07			
		Pump test data: Well water was _____ ft. after _____ hours of pumping @ _____ gpm			
		Est. Yield: _____ gpm Well water was _____ ft. after _____ hours of pumping @ _____ gpm			
		Bore Hole Diameter 12 in. _____ to _____ ft. and _____ in. _____ to _____ ft.			
		WELL WATER TO BE USED AS:			
		1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well			
		2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below)			
Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO					
5	TYPE OF CASING USED: 1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded 2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile Welded Clamped				
Blank casing diameter 8 in. _____ to _____ ft., Dia. _____ in. _____ to _____ ft., Dia. _____ in. _____ to _____ ft.					
Casing height above land surface: 36 in., Weight: _____ lbs. / ft. Wall thickness or gauge No. _____					
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) N/A 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) N/A					
SCREEN - PERFORATION INTERVAL From _____ ft. to _____ ft., From _____ ft. to _____ ft. GRAVEL PACK INTERVALS: From _____ ft. to _____ ft., From _____ ft. to _____ ft.					
6	GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug Grout Intervals: From _____ ft. to _____ ft., From _____ ft. to _____ ft., From 3 ft. to 23 ft. What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below) 3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage None Apparent Direction from well? _____ How many feet?				
From To LITHOLOGIC LOG		From To LITHOLOGIC LOG			
		0	3	compacted clay	
		3	23	bentonite hole plug	
		23	50	chlorinated gravel	
				RECEIVED MAY 10 2007 BUREAU OF WATER	
				CORRECTED	
7	Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 3-7-2007 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 3-9-2007 under the business name of Harp Well and Pump Service by (signature) Todd S. Harp				