

1 LOCATION OF WATER WELL: Sedgwick		FRACTION: NE 1/4 SW 1/4 NE 1/4		SECTION NUMBER 9	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 1W EW
Distance and direction from nearest town or city street address of well if located within city? 1978 N.W. Parkway Wichita, Kansas						
2 WATER WELL OWNER: TRACY, Bob		Board of Agriculture, Division of Water Resource				
RR#,ST. ADDRESS,BOX #: 1978 N.W. Parkway		Application Number:				
CITY, STATE: Wichita, Kansas		ZIP CODE:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 65 ft. ELEVATION:				
1 Mile N W E S		Depth of groundwater Encountered: ft.				
		WELL'S STATIC WATER LEVEL 25 FT. BELOW LAND SURFACE MEASURED ON 4/3/08				
		Pump test data: Well water was ft. after hours of pumping @ gpm				
		Est. Yield: gpm Well water was ft. after hours of pumping @ gpm				
		Bore Hole Diameter 12 in. to 65 ft. and in. to ft.				
WELL WATER TO BE USED AS:		9. Dewatering 11. Injection well				
1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below)						
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well						
Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted		Was Water Well Disinfected? YES NO				
5 TYPE OF CASING USED:		CASING JOINTS: Glued Threaded				
1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below)		Welded Clamped				
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26						
Blank casing diameter 5 in. to 45 ft., Dia. in. to ft., Dia. in. to ft.						
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214						
TYPE OF SCREEN OR PERFORATION MATERIAL:		11. Other (specify)				
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS		12. None used (open hole)				
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement						
SCREEN OR PERFORATION OPENINGS ARE:		11. None (open hole)				
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes		10. Other (specify)				
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut						
SCREEN - PERFORATION INTERVAL From 45 ft. to 65 ft., From ft. to ft., From ft. to ft.						
GRAVEL PACK INTERVALS: From 24 ft. to 65 ft., From ft. to ft., From ft. to ft.						
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug						
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.						
What is the nearest source of possible contamination:		15. Oil well/Gas well				
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage		16. Other (specify below)				
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well						
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage						
Direction from well? East		How many feet? 20 ft. plus				
From To LITHOLOGIC LOG		From To LITHOLOGIC LOG				
0	3	topsoil				
3	20	clay				
20	27	sandy				
27	40	fine sand				
40	45	clay				
45	65	medium sand				
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 4/3/2008 and this record is true to the best of my knowledge and belief.						
Kansas Water Well Contractor's License No. 236		This water well record was completed on (mo/day/year) 4/7/2008				
under the business name of Harp Well and Pump Service		by (signature) Todd S. Harp				