


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Sedgwick	FRACTION NW 1/4 SW 1/4 NE 1/4	SECTION NUMBER 10	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 1W E/W
--	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?
21st and Ridge Road Wichita, Kansas

2 WATER WELL OWNER: SEDGWICK COUNTY PARKS AND RECREATION DEPT.	RR#,ST. ADDRESS,BOX #: 525 N. Main	CITY, STATE: Wichita, Kansas	ZIP CODE: 67203	Application Number: 47006
--	--	--	---------------------------	-------------------------------------

Board of Agriculture, Division of Water Resource

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 45 ft. ELEVATION: Depth of groundwater Encountered: ft. WELL'S STATIC WATER LEVEL 12 FT. BELOW LAND SURFACE MEASURED ON 7/24/08 Pump test data: Well water was ft. after hours of pumping @ gpm Est. Yield: gpm Well water was ft. after hours of pumping @ gpm Bore Hole Diameter 12 in. to 45 ft. and in. to ft. WELL WATER TO BE USED AS: 1. Domestic 2. Irrigation 3. Feedlot 4. Industrial 5. Public water supply 6. Oil field water supply 7. <u>Lawn and garden only</u> 8. Air conditioning 9. Dewatering 10. Monitoring well 11. Injection well 12. Other (Specify below) Was a chemical/bacteriological sample submitted to Department? YES <u>NO</u> ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? <u>YES</u> NO
--	--

5 TYPE OF CASING USED: 1. Steel 2. <u>PVC</u> 3. RPM (SR) 4. ABS 5. Wrought Iron 6. Asbestos-Cement 7. Fiberglass 8. Concrete tile 9. Other (Specify below) SDR-26	CASING JOINTS: <u>Glued</u> Threaded Welded Clamped
--	---

Blank casing diameter **5** in. to **25** ft., Dia. in. to ft., Dia. in. to ft.
Casing height above land surface: **12** in., Weight: **2.35** lbs. / ft. Wall thickness or gauge No. **.214**

TYPE OF SCREEN OR PERFORATION MATERIAL:
1. Steel 2. Brass 3. Stainless Steel 4. Galvanized 5. Fiberglass 6. Concrete Tile 7. PVC 8. RMP (SR) 9. ABS 10. Asbestos-Cement 11. Other (specify) 12. None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
1. Continuous slot 2. Louvered shutter 3. Mill slot 4. Key punched 5. Gauzed wrapped 6. Wire wrapped 7. Torch cut 8. Saw cut 9. Drilled holes 10. Other (specify) 11. None (open hole)

SCREEN - PERFORATION INTERVAL	From 25 ft. to 45 ft.,	From ft. to ft.,	From ft. to ft.,
GRAVEL PACK INTERVALS:	From 24 ft. to 45 ft.,	From ft. to ft.,	From ft. to ft.,

6 GROUT MATERIALS: Grout Intervals: From 4 ft. to 24 ft.,	2. Cement Grout	3. Bentonite	Other bentonite hole plug
--	-----------------	--------------	----------------------------------

What is the nearest source of possible contamination:
1. Septic tank 2. Sewer lines 3. Watertight sewer line 4. Lateral lines 5. Cess Pool 6. Seepage pit 7. Pit privy 8. Sewage lagoon 9. Feed yard 10. Livestock pens 11. Fuel storage 12. Fertilizer storage 13. Insecticide storage 14. Abandon water well 15. Oil well/Gas well 16. Other (specify below) **None Apparent**

Direction from well? How many feet?

From	To	LITHOLOGIC LOG	From	To	LITHOLOGIC LOG
0	3	topsoil			
3	10	clay			
10	14	sandy clay			
14	25	fine sand			
25	45	medium sand			

7 Contractor's or Landowner's Certification: This water well was 1. <u>constructed</u> 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 7/24/2008 and this record is true to the best of my knowledge and belief.	Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 7/28/2008 under the business name of Harp Well and Pump Service by (signature) Todd S. Harp
---	--