

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

1 LOCATION OF WATER WELL:

County: Sedwick NW SE 1/4 NE 1/4 NW 1/4

Section Number

4

Township Number

T 270 S

Range Number

R 1 W

Distance and direction from nearest town or city street address of well if located within city?

2814 N. Fossil Rim

Global Positioning Systems (decimal degrees, min. of 4 digits)

Latitude:

Longitude:

Elevation:

Datum:


Data Collection Method:

2 WATER WELL OWNER:

RR#, St. Address, Box # 2814 N. Fossil Rim
City, State, ZIP Code Wichita

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N



S

4 DEPTH OF COMPLETED WELL 85 ft.

Depth(s) Groundwater Encountered (1) 27 ft. (2) ft. (3) ft.
WELL'S STATIC WATER LEVEL 27 ft. below land surface measured on mo/day/yr. 9/26/08

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial Domestic (lawn & garden) 10 Monitoring wellWas a chemical/bacteriological sample submitted to Department? Yes No ☒; If yes, mo/day/yrSample was submitted Water well disinfected? Yes ☒ No

5 TYPE OF CASING USED:

1 Steel

3 RMP (SR)

5 Wrought Iron

6 Asbestos-Cement

8 Concrete tile

9 Other (specify below)

CASING JOINTS: Glued ☒ Clamped

Welded

Threaded

2 PVC

4 ABS

7 Fiberglass

Blank casing diameter 5 in. to 85 ft., Diameter in. to ft., Diameter in. to ft.

Casing height above land surface 12 in., Weight 140 lbs./ft. Wall thickness or gauge No. 26

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel

3 Stainless Steel

5 Fiberglass

PVC

9 ABS

11 Other (Specify)

2 Brass

4 Galvanized Steel

6 Concrete tile

8 RM (SR)

10 Asbestos-Cement

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

3 Mill slot

5 Gauzed wrapped

7 Torch cut

9 Drilled holes

11 None (open hole)

2 Louvered shutter

4 Key punched

6 Wire wrapped

8 Saw cut

10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 75 ft. to 85 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 24 ft. to 85 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

6 GROUT MATERIAL:

1 Neat cement

2 Cement grout

3 Bentonite

4 Other

Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank

4 Lateral lines

7 Pit privy

10 Livestock pens

13 Insecticide storage

16 Other (specify

2 Sewer lines

5 Cess pool

8 Sewage lagoon

11 Fuel storage

14 Abandoned water well

below)

3 Watertight sewer lines

6 Seepage pit

9 Feedyard

12 Fertilizer storage

15 Oil well/gas well

Direction from well? E How many feet? 15 ft.

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	TOP SOIL			
2	17	Fine Sandy Clay			
17	20	Clay			
20	29	Fine Sand			
29	47	Med Fine Sand			
47	85	Med Course Sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/26/08 and this record is true to the best of my knowledge and belief.Kansas Water Well Contractor's License No. 6611 This Water Well Record was completed on (mo/day/year) 10/3/08under the business name of Chase Drilling by (signature) D. ChaseINSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at <http://www.kdheks.gov/waterwell/index.html>.