

1 LOCATION OF WATER WELL: Sedgwick	FRACTION NE 1/4 NW 1/4 NW 1/4	SECTION NUMBER 18	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 1W E/W	
Distance and direction from nearest town or city street address of well if located within city? 1356 N. Pine Grove Ct. Wichita, Kansas					
2 WATER WELL OWNER: NELSON, Brock RR#,ST. ADDRESS,BOX #: 1356 N. Pine Grove Ct. CITY, STATE: Wichita, Kansas ZIP CODE: _____ Application Number: _____					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 125 ft. ELEVATION: _____			
1 Mile W E		Depth of groundwater Encountered: _____ ft.			
		WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 5/7/09			
		Pump test data: Well water was _____ ft. after hours of pumping @ _____ gpm			
		Est. Yield: _____ gpm Well water was _____ ft. after hours of pumping @ _____ gpm			
Bore Hole Diameter 12 in. to 125 ft. and _____ in. to _____ ft.					
WELL WATER TO BE USED AS:					
1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below)					
Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted					
Was Water Well Disinfected? YES NO					
5 TYPE OF CASING USED:					
1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded 2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26 Welded Clamped					
Blank casing diameter 5 in. to 105 ft., Dia. _____ in. to _____ ft., Dia. _____ in. to _____ ft.					
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .224					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)					
SCREEN - PERFORATION INTERVAL From 105 ft. to 125 ft., From _____ ft. to _____ ft.					
GRAVEL PACK INTERVALS: From 24 ft. to 125 ft., From _____ ft. to _____ ft.					
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug					
Grout Intervals: From 4 ft. to 24 ft., From _____ ft. to _____ ft., From _____ ft. to _____ ft.					
What is the nearest source of possible contamination:					
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below) 3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage					
Direction from well? East How many feet? 10 ft. plus					
LITHOLOGIC LOG					
From	To	Description	From	To	Description
0	4	topsoil			
4	18	clay			
18	30	medium sand			
30	75	clay			
75	95	medium coarse sand			
95	105	clay			
105	125	medium coarse sand			
CORRECTED					
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 5/7/2009 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 5/13/2009 under the business name of Harp Well and Pump Service by (signature) Todd S. Harp					