WATI	R WE	LL RECORD	Form W	VWC-5	Divis	sion of Wate	r Resources App. N	MW-1B	
			Fraction			Number	Township No.		
	inty: Sec		NW 1/4 NW 1/4 NV	W 1/4 NE 1/4	1	9	T 27 S		
		Address of Well Location;			Global I	Positioning	System (GPS) i	information:	
fror	from nearest town or intersection: If at owner's address, check here .						Latitude: .37.72250 N. (in decimal degrees)		
10	1007 E. 21st Street N., Wichita, KS						Longitude: 97.32563 W (in decimal degrees)		
1001 2.210.00000000						Elevation:			
2 WATER WELL OWNER: NIM Inc.						Datum: ☐ WGS 84, ☑ NAD 83, ☐ NAD 27			
14117, 1110.						Collection Method: ☐ GPS unit (Make/Model:)			
at a grad of						☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
City, State, ZIP Code : Clayton, MO 63105						Est. Accuracy: □ <3 m, □ 3-5 m, □ 5-15 m, □ >15 m			
3 LOCATE WELL									
1	WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 37.9 ft.								
SEC	SECTION BOX: Depth(s) Groundwater Encountered (1).12. ft. (2). ft. (3). ft. WELL'S STATIC WATER LEVEL12.6 ft. below land surface measured on mo/day/yr. 04/12/10.								
	WELL'S STATIC WATER LEVEL12.6								
	Pump test data: Well water was								
EST. YIELDgpm. Well water wasft. after hours pumpinggpm									
Bore Hole Diameter 9									
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Domestic Feedlot Oil field water supply Dewatering Other (Specify below)									
SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below) Irrigation Industrial Domestic-lawn & garden Monitoring well									
	Was a chemical/bacteriological sample submitted to Department? Yes V No								
	S If yes, mo/day/yr sample was submitted								
1 mile Water well disinfected? Yes No									
5 TYPE OF CASING USED: Steel PVC Other									
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter									
Casing diameter .2									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
☐ Steel ☐ Stainless Steel ✔ PVC ☐ Other (Specify)									
Brass Galvanized Steel None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)									
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From 10. ft. to37. ft., From									
SCRE	EN-PEKI							to ft.	
	GRAV	EL PACK INTERVALS:							
	OICA V	LETACK INTERVALS.	From	ft to	f	ft., From		to ff	
From									
i	intervals:	From .1 ft. to							
		est source of possible conta				,			
] Septic ta	nk 🔲 Lateral lin	nes 🔲 Pit privy	Livestock] Insecticide	storage 🗹 Otl	her (specify below)	
	Sewer li		Sewage lagoon			Abandoned		apyard & Refinery	
		ht sewer lines		Fertilizer s		Oil well/ga	5 WOII	• • • • • • • • • • • • • • • • • • • •	
		n well	* - I						
FROM		LITHOLOG		FROM	TO I	LITHO. LC	OG (cont.) or PLU	JGGING INTERVALS	
0'	2' 5'	Fill - gravel with clay &	Drick				·		
2' 5'	12'	Clay - gray-black							
12'	36'	Silty Clay - gray Fine to Very Coarse Sa	and brown						
36'	37'	Shale	ilia - Diowii	-					
36	37	Silale		 					
	-								
 	1								
				 					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged									
under my jurisdiction and was completed on (mo/day/year) .04/06/10 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/year)									
		ss name ofTerracon Co						4	
INSTRU	CTIONS:	Use typewriter or ball point pen	. PLEASE PRESS FIRML	Y and PRINT cle	arly. Please	fill in blanks	and check the correct	t answers. Send three copies	
(white, b	lue, pink) t	o Kansas Department of Health	and Environment, Bureau	of Water, Geole	gy Section, I	1000 SW Jac	kson St., Suite 420,	Topeka, Kansas 66612-1367.	
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.									
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy									