

1	LOCATION OF WATER WELL: Sedgwick	FRACTION NE 1/4 NE 1/4 NW 1/4	SECTION NUMBER 18	TOWNSHIP NUMBER T 27 S	RANGE NUMBER R 1W E/W
---	--	---	-----------------------------	----------------------------------	---------------------------------

1337 N. Cardington **Wichita, Kansas**

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: **100** ft. ELEVATION:

Depth of groundwater Encountered: ft.

WELL'S STATIC WATER LEVEL **18** FT. BELOW LAND SURFACE MEASURED ON **8/29/11** mo/day/yr:

Pump test data: Well water was ft. after hours of pumping @ gpm

Est. Yield: gpm Well water was ft. after hours of pumping @ gpm

Bore Hole Diameter **12** in. to **100** ft. and in. to ft.

WELL WATER TO BE USED AS:

1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well

2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted

Was Water Well Disinfected? YES NO

5	TYPE OF CASING USED:		9. Other (Specify below)		CASING JOINTS:		Threaded	
	1. Steel	3. RPM (SR)	5. Wrought Iron	7. Fiberglass		Glued		Clamped
	2. PVC	4. ABS	6. Asbestos-Cement	8. Concrete tile	SDR-26	Welded		
	Blank casing diameter	5 in.	to	80 ft.,	Dia.	in.	to	ft.
	Casing height above land surface:	12 in.,	Weight:	2.35 lbs. / ft.	Wall thickness or gauge No.	.214		
	TYPE OF SCREEN OR PERFORATION MATERIAL:							
	1. Steel	3. Stainless Steel	5. Fiberglass	7. PVC	9. ABS	11. Other (specify)		
	2. Brass	4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. Asbestos-Cement	12. None used (open hole)		
	SCREEN OR PERFORATION OPENINGS ARE:							
	1. Continuous slot	3. Mill slot	5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)		
	2. Louvered shutter	4. Key punched	6. Wire wrapped	8. Saw cut	10. Other (specify)			
	SCREEN - PERFORATION INTERVAL	From	80 ft.	to	100 ft.,	From	ft.	to
		From	ft.	to	ft.,	From	ft.	to
	GRAVEL PACK INTERVALS:	From	24 ft.	to	100 ft.,	From	ft.	to
		From	ft.	to	ft.,	From	ft.	to

6	GROUT MATERIALS:		1. Neat cement		2. Cement Grout		3. Bentonite		Other		bentonite hole plug	
	Grout Intervals:		From	4	ft.	to	24	ft.	From	ft.	to	ft.
	What is the nearest source of possible contamination:											
	1. Septic tank		4. Lateral lines		7. Pit privy		10. Livestock pens		13. Insecticide storage		15. Oil well/Gas well	
2. Sewer lines		5. Cess Pool		8. Sewage lagoon		11. Fuel storage		14. Abandon water well		16. Other (specify below)		
3. Watertight sewer line		6. Seepage pit		9. Feed yard		12. Fertilizer storage						
Direction from well?		South						How many feet?		10 ft. plus		

[illegible]

Todd S. Harp