

1 LOCATION OF WATER WELL:

County: Saline

Fraction $\frac{1}{4}$ NE $\frac{1}{4}$ SE $\frac{1}{4}$ NE $\frac{1}{4}$

Section Number 4

Township No. T 27 S

Range Number R 1 E ☒ W

Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here ☐.

2710 n Springmeadows

2 WATER WELL OWNER: Mr Bidere

RR#, Street Address, Box #: 2710 n Springmeadows

City, State, ZIP Code: White R 67205

3 LOCATE WELL WITH AN "X" IN SECTION BOX:

N

W

-- NW --

☒

-- NE --

-- SW --

-- SE --

E

S

-----1 mile-----

4 DEPTH OF COMPLETED WELL 55 ft.

Depth(s) Groundwater Encountered (1) 2.0 ft. (2) ft. (3) ft.

WELL'S STATIC WATER LEVEL 2.0 ft. below land surface measured on mo/day/yr. 3-5-12

Pump test data: Well water was ft. after hours pumping gpm

EST. YIELD gpm. Well water was ft. after hours pumping gpm

Bore Hole Diameter 9 in. to 2.0 ft., and in. to ft.

WELL WATER TO BE USED AS: ☐ Public water supply ☐ Geothermal ☐ Injection well

☐ Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ Other (Specify below)

☐ Irrigation ☐ Industrial ☒ Domestic-lawn & garden ☐ Monitoring well

Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☒ No

If yes, mo/day/yr sample was submitted.

Water well disinfected? ☐ Yes ☒ No

5 TYPE OF CASING USED: ☐ Steel ☒ PVC ☐ Other

CASING JOINTS: ☒ Glued ☐ Clamped ☐ Welded ☐ Threaded

Casing diameter 5 in. to 4.5 ft., Diameter in. to ft., Diameter in. to ft.

Casing height above land surface 1.2 in., Weight lbs./ft., Wall thickness or gauge No. 160

TYPE OF SCREEN OR PERFORATION MATERIAL:

☐ Steel ☐ Stainless Steel ☒ PVC ☐ Other (Specify)

☐ Brass ☐ Galvanized Steel ☐ None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

☐ Continuous slot ☒ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)

☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut ☐ Other (specify)

SCREEN-PERFORATED INTERVALS: From 4.5 ft. to 5.5 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft.

From ft. to ft., From ft. to ft.

none

6 GROUT MATERIAL: ☐ Neat cement ☒ Cement grout ☐ Bentonite ☐ Other

Grout Intervals: From 0 ft. to 2.0 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below)

☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well

☒ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well

Direction from well West Distance from well 60

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHO. LOG (cont.) or PLUGGING INTERVALS
<u>0</u>	<u>11</u>	<u>Top Soil</u>			
<u>11</u>	<u>33</u>	<u>Fine Tan Sand</u>			
<u>33</u>	<u>55</u>	<u>Coarse Tan Sand</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, ☐ reconstructed, or ☐ plugged under my jurisdiction and was completed on (mo/day/year) 3-5-12 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 477 This Water Well Record was completed on (mo/day/year) 3-5-12

under the business name of Beardan Pump & Well by (signature) David Beard

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at <http://www.kdheks.gov/waterwell/index.html>.