

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number			
County: <u>Sedgwick</u>		<u>S10 1/4 NW 1/4 NW 1/4</u>		<u>18</u>		<u>270</u> S		<u>10</u> E W			
Distance and direction from nearest town or city street address of well if located within city? <u>11809 W. Alderney Ct.</u>											
2 WATER WELL OWNER: <u>Orvis Construction</u>											
RR#, St. Address, Box #: <u>950 N. Tyler Suite # 2</u>											
City, State, ZIP Code: <u>Wichita, KS 67212</u>											
Board of Agriculture, Division of Water Resources Application Number:											
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL		ft. ELEVATION:							
		Depth(s) Groundwater Encountered		ft. 2.		ft. 3.		ft.			
		WELL'S STATIC WATER LEVEL		<u>27</u>		ft. below land surface measured on mo/day/yr		<u>7-31-98</u>			
		Pump test data: Well water was		ft. after		hours pumping		gpm			
		Est. Yield <u>20</u> gpm: Well water was		ft. after		hours pumping		gpm			
		Bore Hole Diameter		in. to <u>96</u>		ft. and		in. to		ft.	
WELL WATER TO BE USED AS:											
1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Monitoring well											
Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u>X</u> ; If yes, mo/day/yr sample was submitted											
Water Well Disinfected? Yes <u>X</u> No											
5 TYPE OF BLANK CASING USED:											
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded											
Blank casing diameter <u>5</u> in. to <u>86</u> ft. Dia. <u>2.40</u> in. to <u>160</u> ft. Dia.											
Casing height above land surface <u>12</u> in., weight <u>2.40</u> lbs./ft. Wall thickness or gauge No. <u>160 PSI</u>											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)											
SCREEN-PERFORATED INTERVALS:											
From <u>86</u> ft. to <u>96</u> ft. From <u>27</u> ft. to <u>96</u> ft. GRAVEL PACK INTERVALS: From <u>27</u> ft. to <u>96</u> ft.											
6 GROUT MATERIAL:											
1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout intervals: From <u>27</u> ft. to <u>96</u> ft. From <u>27</u> ft. to <u>96</u> ft.											
What is the nearest source of possible contamination:											
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage											
Direction from well? <u>southeast</u> How many feet? <u>30</u>											
FROM		TO		LITHOLOGIC LOG		FROM		TO		PLUGGING INTERVALS	
0		17		clay							
17		28		sand							
28		80		clay							
80		96		gravel							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>7-31-98</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>318</u> This Water Well Record was completed on (mo/day/yr) <u>7-31-98</u> under the business name of <u>Weninger Drilling Inc.</u> by (signature) <u>Michelle Georges</u>											